


2020–
2024

arXiv:2606.26354v2 [quant-ph] 26 Sep 2026

Equivalence of non-local computation tasks beyond Clifford operations

Andreas Bluhm[1], Simon Höfer[1], Alex May[2,3], Florian Speelman[4], and Philip Verduyn Lunel[5]

[1]Univ. Grenoble Alpes, CNRS, Grenoble INP, LIG
[2]Perimeter Institute for Theoretical Physics
[3]Institute for Quantum Computing, Waterloo, Ontario
[4]QuSoft, University of Amsterdam
[5]Sorbonne Université, CNRS, LIP6, Paris

Non-local quantum computation (NLQC) studies how two collaborating players can implement channels on distributed systems using a single simultaneous round of quantum communication and shared entanglement. NLQC has applications in diverse areas, ranging from quantum position-verification to quantum gravity. Recently, it has been realized that the relationships among families of NLQC tasks are highly structured: many seemingly distinct tasks are related by reductions, wherein implementations of one task can be used to efficiently implement a second task. This is analogous to the notion of reduction in complexity theory, and reveals the relative hardness of NLQC tasks. In this work we continue the study of reductions among NLQC tasks. We focus on NLQC examples of the greatest interest in quantum position-verification; in particular examples involving large classical inputs and fixed-size quantum inputs, since these constitute the most feasible protocols for position-verification schemes. Within this setting, we find many new relationships among NLQC tasks. For instance, protocols for the simplest example of redirecting a quantum system based on a classical control imply protocols for controlled single qubit measurements in arbitrary bases, the controlled application of any Clifford unitary, and even the controlled application of any unitary of the form $U = C_1 D C_0$ with D an arbitrary diagonal unitary and C_0, C_1 Clifford circuits. This implies that many feasible position-verification schemes have the same asymptotic scaling for their entanglement cost, and hence a similar level of security. Our techniques rely on ideas from gate teleportation and measurement based quantum computation, among other areas, bringing several new strategies into NLQC which may be of independent interest.

Contents

1 Introduction **2**
1.1 Previous work . . . 4
1.2 Our results . . . 5

2 Preliminaries **7**
2.1 Tools from quantum information theory . . . 7
2.2 Non-local quantum computation . . . 8
2.3 NLQC reductions . . . 9

Andreas Bluhm: andreas.bluhm@univ-grenoble-alpes.fr
Simon Höfer: simon.hofer@univ-grenoble-alpes.fr
Alex May: amay@perimeterinstitute.ca
Florian Speelman: f.speelman@uva.nl
Philip Verduyn Lunel: philip.verduyn-lunel@lip6.fr