



2022–
2024

Sample complexity of quantum resource testing via one-shot quantum blurring

Dmitry Grinko[1,2,3] and Ludovico Lami[4]

[1]*QuSoft, Amsterdam, The Netherlands*

[2]*Institute for Logic, Language and Computation, University of Amsterdam, Amsterdam, the Netherlands*

[3]*Korteweg-de Vries Institute for Mathematics, University of Amsterdam, Amsterdam, the Netherlands*

[4]*Scuola Normale Superiore, Piazza dei Cavalieri 7, 56126 Pisa, Italy*

(Dated: August 19, 2026)

Quantum resource testing is a fundamental primitive of quantum information processing, profoundly connected to resource manipulation. Its goal is to discriminate n copies of a given resourceful state ρ from all free (i.e., resourceless) states; key instances for applications are entanglement testing and quantum magic testing. The asymptotic characterisation relies on the recently proven Generalised Quantum Stein's Lemma (GQSL), which establishes the rate of decay of the false negative error probability for a fixed false positive error probability. This result, however, is intrinsically asymptotic and thus can provide no finite-resource guarantees, which makes its practical implications unclear. Here, we establish the first rigorous finite-n bounds on quantum resource testing and hence quantum resource manipulation, thus strengthening the GQSL and providing explicit estimates on the number of copies needed to achieve a prescribed performance. As notable consequences, we obtain (a) the convergence of the regularised Rényi relative entropies of a resource, which settles the important open problem from [Fang/Hayashi, IEEE ToIT 72:6, 2026]; and (b) the first sample-complexity bound for asymmetric resource testing: for any fixed false positive error probability, a false negative error probability of at most δ can be achieved with $n = O\left(\frac{\log(1/\delta)}{D^{\infty}(\rho\|\mathscr{F})}\right)$ copies of ρ, in the limit where $\delta \to 0$.

arXiv:2607.24712v2 [quant-ph] 19 Aug 2026

I. INTRODUCTION

Entanglement is at the same time one of the most puzzling quantum phenomena, which has bewildered scientists for more than a century, and one of the essential ingredients of quantum technologies. For these reasons, its detection and manipulation are two of the most fundamental primitives of quantum information science. And yet, in spite of their importance, the ultimate limitations to these tasks remain largely mysterious.

Furthermore, the rapid progress of quantum technologies has uncovered a whole landscape of different quantum resources, whose detection and manipulation are also critical to different applications. A notable example, besides entanglement, is nonstabiliser-ness, a.k.a. 'quantum magic', which works as fuel for universal quantum computation [1]. To tackle the proliferation of quantum resources, a unified paradigm for their understanding, i.e. the formalism of quantum resource theories [2], has been developed. In this paper, we will formulate our results in terms of general quantum resources, but all of them apply to entanglement, magic, and many other examples.

In a quantum resource theory, one identifies a set of 'free states', whose preparation is assumed to be experimentally inexpensive; any other state is called 'resourceful', as it contains some amount of the quantum resource under examination. For example, in entanglement theory separable (a.k.a. unentangled) states are considered as free, and any other (entangled) state is resourceful. Together with free states, one also specifies a notion of 'free operations', namely op-