


A Quantum Algorithm for *st*-Transport on Flat Connection Graphs

Stacey Jeffery[1,2], Tobias J. Osborne[3], and Galina Pass[1]

[1]QuSoft & CWI, Amsterdam
[2]QLever & University of Amsterdam
[3]Institut für Theoretische Physik and L3S Research Center, Leibniz Universität Hannover

arXiv:2609.40231v1 [quant-ph] 30 Sep 2026

Abstract

We study a generalization of undirected *st*-connectivity to graphs whose edges carry quantum operations. Let $G = (V, E)$ be an undirected graph on n vertices in which each edge $\{u, v\}$ is labeled by a unitary $U_{uv} \in \mathbb{C}^{k\times k}$, with $U_{vu} = U_{uv}^\dagger$. We assume the labels form a *flat* connection: the ordered product of labels along any path between a pair of vertices u and v is independent of the path. Equivalently, the connection is pure gauge, i.e., gauge-equivalent to the trivial connection; such graphs are exactly the consistent connection graphs of spectral graph theory and the noiseless instances of group synchronization. Consequently, whenever s and t are connected, transporting a state from s to t defines a unique unitary $U_s(t)$. Given states $|\psi_s\rangle, |\psi_t\rangle \in \mathbb{C}^k$ and an oracle that returns the neighbours of a vertex while coherently applying the corresponding edge unitaries, the *st-transport problem* is to decide whether s and t are connected and, if so, to estimate the squared overlap between $U_s(t)|\psi_s\rangle$ and $|\psi_t\rangle$ to additive error ε. When $k = 1$ and all labels are trivial, this is exactly undirected *st*-connectivity. We give a bounded-error quantum algorithm for *st*-transport that runs in time $\widetilde{O}(n/\varepsilon)$ and uses $O(\log n + \log k + \log(1/\varepsilon))$ space. We do this by designing a transducer and applying a Metropolis-Hastings reweighting to the input graph. We also prove an $\Omega(n)$ quantum query lower bound that holds even when s and t are promised to be connected, so for constant ε our algorithm is optimal up to polylogarithmic factors.

1 Introduction

A *unitary-labeled graph*, also referred to as a *connection graph* [SW12, BSS13], is a graph in which each edge is equipped with a unitary operator acting on a fixed internal Hilbert space. Such graphs naturally encode how quantum states transform when transported between adjacent vertices.

The idea of decorating the edges of a graph with unitaries originates in fundamental physics. In order to explain the confinement of quarks, Wilson proposed regulating quantum chromodynamics on a discrete spacetime lattice [Wil74]: here the gauge field is nothing other than an assignment of a unitary parallel transporter to each edge, and all gauge-invariant physical information is carried by the ordered products of these unitaries along paths, the eponymous *Wilson loops*. (For discrete gauge groups this construction was foreshadowed by Wegner's generalised Ising models [Weg71].) Thus was born *lattice gauge theory* [Kog79, Cre83], which, particularly in the Hamiltonian formulation of Kogut and Susskind [KS75], is precisely the study of quantum states transported along the edges of a unitary-labeled graph.

A most successful tool in the study of lattice gauge theory has been the computer. Monte Carlo sampling of the euclidean path integral, pioneered by Creutz [Cre80], supplied the first convincing numerical evidence for the coexistence of confinement and asymptotic freedom, and three decades of refinement culminated in the ab initio determination of the light hadron spectrum [DFF+08], a landmark quantitative confirmation of the standard model. This success is not, however, unqualified: the sign problem afflicting such sampling is NP-hard [TW05], and the regimes where importance sampling fails — notably real-time dynamics and finite fermion density — remain largely beyond the reach of classical computation.

These obstructions have made gauge theory a natural proving ground for quantum computation. Quantum algorithms for simulating Kogut–Susskind Hamiltonians were proposed early on [BY06], the