

2024


Nondeterministic quantum communication complexity: the cyclic equality game and iterated matrix multiplication

Harry Buhrman[1], Matthias Christandl[2], Jeroen Zuiddam[1]

April 5, 2016

arXiv:1603.03757v2 [quant-ph] 2 Apr 2016

Abstract

We study nondeterministic multiparty quantum communication with a quantum generalization of broadcasts. We show that, with number-in-hand classical inputs, the communication complexity of a Boolean function in this communication model equals the logarithm of the *support rank* of the corresponding tensor, whereas the approximation complexity in this model equals the logarithm of the *border support rank*. This characterisation allows us to prove a log-rank conjecture posed by Villagra et al. for nondeterministic multiparty quantum communication with message passing.

The support rank characterization of the communication model connects quantum communication complexity intimately to the theory of asymptotic entanglement transformation and algebraic complexity theory. In this context, we introduce the *graphwise equality problem*. For a cycle graph, the complexity of this communication problem is closely related to the complexity of the computational problem of multiplying matrices, or more precisely, it equals the logarithm of the support rank of the iterated matrix multiplication tensor. We employ Strassen's laser method to show that asymptotically there exist nontrivial protocols for every odd-player cyclic equality problem. We exhibit an efficient protocol for the 5-player problem for small inputs, and we show how Young flattenings yield nontrivial complexity lower bounds.

1. Introduction

Let $f : X \times Y \times Z \to \{0,1\}$ be a function on a product of finite sets X, Y and Z. Alice, Bob and Charlie have to compute f in the following sense. Alice receives an $x \in X$, Bob receives a $y \in Y$ and Charlie receives a $z \in Z$, and each player receives a private random bit string. Then the players communicate in rounds. Each round, one player communicates by broadcasting a bit to the other players. After these rounds of communication, each player has to output a bit, such that if $f(x,y,z) = 1$, then with some nonzero probability all players output 1 and if $f(x,y,z) = 0$, then with probability zero all players output 1. The complexity of such a protocol is the number of broadcasts in the protocol, and we denote the minimum complexity of all such protocols by $\mathrm{N}(f)$.

[1]QuSoft, CWI Amsterdam and University of Amsterdam, Science Park 123, 1098 XG Amsterdam, Netherlands. Email: buhrman@cwi.nl, j.zuiddam@cwi.nl

[2]Department of Mathematical Sciences, University of Copenhagen, Universitetsparken 5, 2100 Copenhagen Ø, Denmark. Email: christandl@math.ku.dk