

2024

QuSoft is named on page 20 of the paper.

Provably secure key establishment against quantum adversaries

Aleksandrs Belovs[1], Gilles Brassard[2,3], Peter Høyer[4], Marc Kaplan[5], Sophie Laplante[6], and Louis Salvail[2]

[1]University of Latvia, stiboh@gmail.com
[2]DIRO, Université de Montréal, {brassard, salvail}@iro.umontreal.ca
[3]Canadian Institute for Advanced Research
[4]Department of Computer Science, University of Calgary, hoyer@ucalgary.ca
[5]School of Informatics, University of Edinburgh, kapmarc@gmail.com
[6]IRIF, Université Paris Diderot, laplante@irif.fr

arXiv:1704.08182v2 [quant-ph] 28 Apr 2017

26 April 2017

Abstract

At Crypto 2011, some of us had proposed a family of cryptographic protocols for key establishment capable of protecting quantum *and classical* legitimate parties unconditionally against a *quantum* eavesdropper in the query complexity model. Unfortunately, our security proofs were unsatisfactory from a cryptographically meaningful perspective because they were sound only in a worst-case scenario. Here, we extend our results and prove that for any $\varepsilon > 0$, there is a classical protocol that allows the legitimate parties to establish a common key after $O(N)$ expected queries to a random oracle, yet any quantum eavesdropper will have a vanishing probability of learning their key after $O(N^{1.5-\varepsilon})$ queries to the same oracle. The vanishing probability applies to a typical run of the protocol. If we allow the legitimate parties to use a quantum computer as well, their advantage over the quantum eavesdropper becomes arbitrarily close to the quadratic advantage that classical legitimate parties enjoyed over classical eavesdroppers in the seminal 1974 work of Ralph Merkle. Along the way, we develop new tools to give lower bounds on the number of quantum queries required to distinguish two probability distributions. This method in itself could have multiple applications in cryptography. We use it here to study average-case quantum query complexity, for which we develop a new composition theorem of independent interest.

1 Introduction

Not taking classified work within secret services into consideration [27], Ralph Merkle is the first person to have asked—and solved—the question of secure communications over insecure channels [23]. In his seminal (rejected!) 1974 project for a Computer Security course at the University of California, Berkeley, he discovered that it is possible for two people who want to communicate securely to establish a secret key by communicating over an authenticated channel that provides no protection against eavesdropping. Merkle's solution to this conundrum offers *quadratic security* in the sense that if the legitimate parties—codenamed Alice and Bob—are willing to expend an effort in the order of N, for some security parameter N, they can establish a key that no eavesdropper—codenamed Eve—can discover with better than vanishing probability without expending an effort in the order of N^2.