

2024



QuSoft is named on page 29 of the paper.

A SINGLE-QUBIT POSITION VERIFICATION PROTOCOL THAT IS SECURE AGAINST MULTI-QUBIT ATTACKS[1]

ANDREAS BLUHM, MATTHIAS CHRISTANDL, AND FLORIAN SPEELMAN

arXiv:2104.06301v3 [quant-ph] 23 Jan 2023

The position of a device or agent is an important security credential in today's society, both online and in the real world. Unless in direct proximity, however, the secure verification of a position is impossible without further assumptions. This is true classically [1], but also in any future quantum-equipped communications infrastructure [2]. We show in this work that minimal quantum resources, in the form of a single qubit, combined with classical communication are sufficient to thwart quantum adversaries that pretend to be at a specific position and have the ability to coordinate their action with entanglement. More precisely, we show that the adversaries using an increasing amount of entanglement can be combatted solely by increasing the number of classical bits used in the protocol. The presented protocols are noise-robust and within reach of current quantum technology.

The difficulty in achieving the verification of a position is best appreciated by considering certain secure-looking protocols and then understanding how they can be broken. For simplicity of the presentation we will consider the verification of the position of an untrusted agent being at midpoint between two verifiers. A protocol for position verification consists of the verifiers each sending messages to the agent who is asked to send responses back. The verification is successful if the responses satisfy certain conditions and if the timing of the signals is right (say in accordance with the speed of light) (see Figure 1).

A first attempt for a secure protocol could consist of a Boolean function f taking the message x from verifier 0 and y (both n-bit strings) from verifier 1 as input and sending the bit $f(x, y)$ back to the verifiers. In order for the agent to return the correct answer, clearly (for most functions f) both x and y are needed, but if the agent was not at midpoint but, say, closer to verifier 0, the agent could never both receive y and send the answer back to verifier 1 in time. Indeed, breaking the protocols entails not one attacking agent, but two, one of which is closer to verifier 0 and one which is closer to verifier 1. Customarily called Alice and Bob, the attacking agents both intercept the input from the verifier they are closest to. Each keeps a copy and forwards another copy of the input to the other partner in crime. When they hold both inputs in hand, they compute the function and return the function value just in time to their respective verifiers (see Figure 1).

This simple attack is indeed the basis of why position verification is not possible in the classical world. Note, however, that the attack directly uses the copying of information. This opens up the possibility of devising protocols based on the exchange of quantum information instead, whose copying is more restricted due to the no-cloning theorem [3, 4]. As Alice and Bob can agree on an attack strategy prior to the start of the protocol, however, they can also distribute entangled particles in order to later coordinate their action. Still, has the balance now tipped and position verification become possible? The plain answer is no [2], as Alice and Bob can immediately upon receipt of the quantum particles engage in an elaborate scheme of back and forth teleportation (with only a single round of crossing classical communication), known as instantaneous non-local

Date: January 24, 2023.

[1]This version of the article has been accepted for publication, after peer review and is subject to Springer Nature's AM terms of use, but is not the Version of Record and does not reflect post-acceptance improvements, or any corrections. The Version of Record is available online at: https://doi.org/10.1038/s41567-022-01577-0