

2024

quantum reports

MDPI

Article

Simple and Rigorous Proof Method for the Security of Practical Quantum Key Distribution in the Single-Qubit Regime Using Mismatched Basis Measurements

Michel Boyer [1], **Gilles Brassard** [1,2], **Nicolas Godbout** [3], **Rotem Liss** [1,4,*], **and Stéphane Virally** [3]

[1] Département IRO, Université de Montréal, 2920 Chemin de la Tour, Montréal (Québec) H3T 1N8, Canada
[2] QuSoft, CWI Amsterdam, Science Park 123, 1098 XG Amsterdam, The Netherlands
[3] Polytechnique Montréal, Department of Engineering Physics, 2500 Chemin de Polytechnique, Montréal (Québec) H3T 1J4, Canada
[4] ICFO—Institut de Ciencies Fotoniques, The Barcelona Institute of Science and Technology, Av. Carl Friedrich Gauss 3, 08860 Castelldefels (Barcelona), Spain
* Correspondence: rotem.liss@icfo.eu

Abstract: Quantum key distribution (QKD) protocols aim at allowing two parties to generate a secret shared key. While many QKD protocols have been proven unconditionally secure in theory, practical security analyses of experimental QKD implementations typically do not take into account all possible loopholes, and practical devices are still not fully characterized for obtaining tight and realistic key rates. We present a simple method of computing secure key rates for any practical implementation of discrete-variable QKD (which can also apply to measurement-device-independent QKD), initially in the single-qubit lossless regime, and we rigorously prove its unconditional security against any possible attack. We hope our method becomes one of the standard tools used for analysing, benchmarking, and standardizing all practical realizations of QKD.

Keywords: quantum key distribution; practical implementations; security; proof

arXiv:2208.13754v3 [quant-ph] 3 Jul 2023

check for updates

Citation: Boyer, M.; Brassard, G.; Godbout, N.; Liss, R.; Virally, S. Simple and Rigorous Proof Method for the Security of Practical Quantum Key Distribution in the Single-Qubit Regime Using Mismatched Basis Measurements. *Quantum Rep.* **2023**, *5*, 52–76. https://doi.org/10.3390/quantum5010005

Received: 30 November 2022
Accepted: 6 January 2023
Published: 18 January 2023

Publisher's Note: MDPI stays neutral with regard to jurisdictional claims in published maps and institutional affiliations.

Copyright: © 2023 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/licenses/by/4.0/).

1. Introduction

The purpose of quantum key distribution (QKD) is to allow two legitimate parties, typically named Alice and Bob, to generate an information-theoretically secure key [1]. Most QKD protocols have been proven secure even if the adversary Eve is allowed to apply any theoretical attack allowed by the laws of quantum theory. However, despite enormous progress in recent years, unconditional security of practical implementations of QKD has remained elusive.

The difficulty of achieving practical security stems from the fact that practical implementations deviate from the theoretical protocols in many important aspects. The theoretical models of the preparation devices, the transmitted quantum systems, the quantum channels, and the measurement devices differ enormously from any experimental realization, and these differences open up loopholes and weaknesses that Eve may be able to exploit (see, e.g., [2,3]).

Most security weaknesses of the measurement devices can be closed using *measurement-device-independent* (MDI) QKD [4–7]. However, MDI QKD still requires us to trust the preparation devices of Alice and Bob, and deviations of the actually prepared quantum states from the theoretical states still pose a significant security threat. Alternatively, in *(fully) device-independent* (DI) QKD [8–10], Alice's and Bob's devices are completely uncharacterized, and violations of Bell's inequality prove the secrecy of the final key. This method, while promising and theoretically solid, still achieves far worse secret key rates than standard QKD (including MDI QKD) in realistic experimental settings [11–13]; in addition, it still requires assumptions, including the assumption that Alice's and Bob's uncharacterized devices are never allowed to communicate with each other or with Eve. Therefore, while we believe that both DI QKD and standard (especially MDI) QKD are important directions that can lead to practical security (perhaps in different levels of security), in this paper, we focus on standard and MDI QKD protocols, where the most pressing practical security problem that has no fully available solution is imperfectly generated quantum states.