

2024

QuSoft is named on page 29 of the paper.

arXiv:2512.02760v1 [quant-ph] 2 Dec 2025

Fault-tolerant quantum computation with constant overhead for general noise

Matthias Christandl[1], Omar Fawzi[2], and Ashutosh Goswami[1]

[1]Department of Mathematical Sciences, University of Copenhagen, Denmark
[2]Université de Lyon, Inria, ENS de Lyon, UCBL, LIP, France

christandl@math.ku.dk, omar.fawzi@ens-lyon.fr, akg@math.ku.dk

Abstract

Fault-tolerant quantum computation traditionally incurs substantial resource overhead, with both qubit and time overheads scaling polylogarithmically with the size of the computation. While prior work by Gottesman showed that constant qubit overhead is achievable under stochastic noise using quantum low-density parity-check (QLDPC) codes, it has remained an open question whether similar guarantees hold under more general, non-stochastic noise models. In this work, we address this question by considering a general circuit-level noise model defined via the diamond norm, which captures both stochastic and non-stochastic noise, including coherent and amplitude damping noise. We prove that constant qubit overhead fault-tolerant quantum computation is achievable in this general setting, using QLDPC codes with constant rate and linear minimum distance. To establish our result, we develop a fault-tolerant error correction scheme and a method for implementing logic gates under general circuit noise. These results extend the theoretical foundations of fault-tolerant quantum computation and offer new directions for fault-tolerant architectures under realistic noise models.

1 Introduction

Fault tolerance is essential for large-scale quantum computations due to the inherently noisy nature of quantum systems [Pre98; Got10]. A leading approach to fault-tolerant quantum computation is based on active error correction, where logical qubits encoded in the code space of an error-correcting code are created using many noisy physical qubits. Using fault-tolerant procedures, one can realize logic gates in the code space of the error-correcting code. The celebrated threshold theorem states that by doing active error correction, it is possible to realize arbitrarily long finite quantum computations with classical input and output, given that the noise rate in the quantum circuit is below a threshold value [AB97; Kit97; AGP06]. Fault-tolerance, however, comes at a price of increased qubit count compared to the noiseless protocol. More precisely, to realize a quantum circuit, one replaces it with a fault-tolerant quantum circuit, which operates on a much larger number of qubits. Therefore, it is of interest from a practical