



2022–
2025



2026

Encoding a bosonic mode into qubits for simulating boson-matter interactions

Maarten Stroeks,[1] Jelena Mackeprang,[2] Yaroslav Herasymenko,[3] and Barbara Terhal[1]

[1] *Delft Institute of Applied Mathematics & QuTech, TU Delft, Delft, The Netherlands*
[2] *QuSoft and CWI, Science Park 123, 1098XG Amsterdam, The Netherlands*
[3] *Perimeter Institute for Theoretical Physics, Waterloo, Ontario N2L 2Y5, Canada*

We explore the space-time cost of encoding of a bosonic mode into a set of qubits via various encodings, and their resilience to noise. In particular, we compare the performance of the unary Fock state encoding, an unexplored encoding of Fock states into Dicke states ("Dicke" encoding), and the binary quadrature encoding. We do so by considering a displacement as well as a simulation of a Dicke model, coupling a bosonic mode to a set of atoms represented as qubits. Using classical simulations, we assess the accuracy and optimized space-time costs in terms of number of qubits, circuit depth and CNOT count of a quantum simulation of the time dynamics using these encodings. Although our study is far from comprehensive, we find that the binary quadrature encoding is overall most favorable in terms of being very space-efficient and relatively time-efficient due to the use of the quantum Fourier transform. Our novel Dicke encoding leads to very shallow circuits, but pays in terms of using many more qubits. We probe the use of an H2-2 Quantinuum trapped-ion qubit device (56 qubits) for displacement and Dicke model simulation in the low boson-number regime, where we find that noise leads to visible deviations from ideal circuit dynamics.

arXiv:2610.29762v1 [quant-ph] 21 Oct 2026

CONTENTS

I. Introduction 1

II. Encoding a bosonic mode into a set of qubits 2
A. Unary Fock encoding 2
B. Binary Fock encoding 2
C. Dicke encoding 3
D. Binary quadrature encoding 4
E. Displacement: encoding error and cost 4
1. Displacement: encoding error 4
2. Displacement: circuit realization 4
3. Comparison with binary Fock encoding 5
4. Comparison between encodings, including circuit depth and CNOT count 6
F. Free bosonic dynamics in the three encodings 6
G. Other bosonic interactions 7

III. Time evolution with the Dicke Hamiltonian 7
A. Dicke Hamiltonian 7
B. Circuit decompositions for quantum simulation 8
1. Edge coloring 8
2. Atom-qubit controlled displacement: minimizing depth 9
C. Numerics: comparison between encodings for Dicke model time evolution 9
1. Output: expected boson number 9
2. Resource estimates 9
3. Numerical results 10

IV. Experiments on the H2-2 Quantinuum Device 11
A. Displacement experiments 11
B. Time evolution of the Dicke model 12

V. Discussion 13
A. Other benchmarks 13
B. Use of rotating or interaction frame 13
C. Different encodings 13
D. Logical bosons? 14
1. Using physical qudits of dimension $\mathsf{d} = 2^{\mathsf{m}}$ 14
2. Using physical bosonic modes 14

VI. AI statement and code & data availability 14

VII. Acknowledgements 15
A. Contributions 15

References 15

A. Trotter bound: displacement 17

B. Preparing the vacuum state in the binary quadrature encoding 17

C. Costings for Dicke Hamiltonian evolution: circuit decompositions and Trotter error bounds 19
1. Dicke encoding 19
2. Unary Fock encoding 20
3. Binary quadrature encoding 21

D. Supplementary information about the H2-2 Quantinuum device experiments 21
1. Compiled depth comparison 22
2. Error analysis 22

I. INTRODUCTION

Quantum simulation of many-body fermionic and bosonic systems is a prime candidate for the use of a quantum computer [1]. While fermions in second-quantized language fairly neatly map onto multi-qubit systems, bosonic degrees of freedom are mathematically