2021–
2025

Sharp error tolerance of the monogamy-of-entanglement game

Llorenç Escolà-Farràs[1,2] and Florian Speelman[1,2]

[1] *QuSoft, CWI Amsterdam, The Netherlands*
[2] *University of Amsterdam, Amsterdam, The Netherlands*

arXiv:2611.09504v1 [quant-ph] 6 Nov 2026

Abstract

The BB84 monogamy-of-entanglement (MoE) game has numerous applications in quantum cryptography, including quantum key distribution, position verification, and unclonable encryption. In this short note, we improve the error threshold for parallel repetition with identical answer strings from the approximately 3.7% certified by the original bound to the sharp threshold $(1 - 1/\sqrt{2})/2 \approx 14.64\%$. When the players need not give identical answers, we also obtain exponential decay whenever the sum of their error tolerances is below this threshold. These bounds strengthen existing security reductions to the BB84 MoE game, improving security bounds and certified noise tolerances for cryptographic protocols.

1 Introduction

Monogamy-of-entanglement (MoE) games describe the limits on two separated players' ability to predict the outcome of a quantum measurement. The BB84 MoE game, introduced by Tomamichel, Fehr, Kaniewski, and Wehner [TFKW13], was used to prove security of quantum position verification and one-sided device-independent quantum key distribution. It also underpins the security analysis of unclonable encryption introduced by Broadbent and Lord [BL20], with further connections developed by Ananth and Kaleoglu [AK21]. The wider framework includes monogamy games for subspace coset states, with applications to unclonable decryption and copy-protection of pseudorandom functions [CLLZ21, CV22]. A leaky variant of the coset-state game has also been used for unclonable encryption with interactive decryption, unclonable bit string commitments, and receiver-independent quantum key distribution [BC23]. More broadly, MoE games were generalized to extended nonlocal games by Johnston, Mittal, Russo, and Watrous [JMRW16].

In the BB84 MoE game, two separated players prepare a shared state with the referee, who measures a qubit in a uniformly chosen computational or Hadamard basis. After learning the basis, both players must guess the referee's outcome without communicating. The optimal probability of winning all n parallel repetitions, over all quantum strategies, is

$$\lambda^n, \qquad \text{where} \quad \lambda = \frac{1}{2} + \frac{1}{2\sqrt{2}}. \tag{1}$$

This holds for arbitrary shared states and local measurements depending on the entire string of basis choices.

For applications that tolerate noise, the players may instead be allowed a bounded number of errors. We first consider the version in which they must give *identical answer strings*, with their common answer differing from the referee's string in at most $\lfloor \gamma n \rfloor$ positions. This winning condition models cryptographic settings in which inconsistent answers lead to rejection, as in position verification. For this version, the counting argument in Section III.B of [TFKW13] gives

$$\Pr[\text{win}] \leq \left(\sum_{j=0}^{\lfloor \gamma n \rfloor} \binom{n}{j} \right) \lambda^n \leq \left(2^{h_2(\gamma)} \lambda\right)^n, \qquad 0 \leq \gamma \leq \tfrac{1}{2}, \tag{2}$$