



2018–
2024



The Quantum Strong Exponential-Time Hypothesis

Harry Buhrman*‡ harry.buhrman@cwi.nl

Subhasree Patro*‡ subhasree.patro@cwi.nl

Florian Speelman ‡ f.speelman@cwi.nl

*University of Amsterdam, ‡QuSoft, CWI Amsterdam

arXiv:1911.05686v2 [quant-ph] 14 Nov 2019

Abstract

The strong exponential-time hypothesis (SETH) is a commonly used conjecture in the field of complexity theory. It states that CNF formulas cannot be analyzed for satisfiability with a speedup over exhaustive search. This hypothesis and its variants gave rise to a fruitful field of research, fine-grained complexity, obtaining (mostly tight) lower bounds for many problems in P whose unconditional lower bounds are hard to find. In this work, we introduce a framework of Quantum Strong Exponential-Time Hypotheses, as quantum analogues to SETH.

Using the QSETH framework, we are able to translate quantum query lower bounds on black-box problems to conditional quantum time lower bounds for many problems in BQP. As an example, we illustrate the use of the QSETH by providing a conditional quantum time lower bound of $\Omega(n^{1.5})$ for the Edit Distance problem. We also show that the n^2 SETH-based lower bound for a recent scheme for Proofs of Useful Work, based on the Orthogonal Vectors problem holds for quantum computation assuming QSETH, maintaining a quadratic gap between verifier and prover.

1 Introduction

There is a rich diversity of problems that can be solvable in polynomial time, some that have surprisingly fast algorithms, such as the computation of Fourier transforms or solving linear programs, and some for which the worst-case run time has not improved much for many decades. Of the latter category Edit Distance is a good example: this is a problem with high practical relevance, and an $O(n^2)$ algorithm using dynamic programming, which is simple enough to be taught in an undergraduate algorithms course, has been known for many decades. Even after considerable effort, no algorithm has been found that can solve this problem in fewer than $O(n^2/\log^2 n)$ steps [MP80], still a nearly quadratic run time.

Traditionally, the field of complexity theory has studied the time complexity of problems in a relatively coarse manner – the class P, the problems solvable in polynomial time, is one of the central objects of study in complexity theory.

Consider CNF-SAT, the problem of whether a formula, input in conjunctive normal form, has a satisfying assignment. What can complexity theory tell us about how hard it is to solve this problem? For CNF-SAT, the notion of NP-completeness gives a convincing reason why it is hard to find a polynomial-time algorithm for this problem: if such an algorithm is found, all problems in the complexity class NP are also solvable in polynomial time, showing P = NP.

Not only is no polynomial-time algorithm known, but (if the clause-length is arbitrarily large) no significant speed-up over the brute-force method of trying all 2^n assignments is known. Impagliazzo,