


2018–
2024


Matching Triangles and Triangle Collection: Hardness based on a Weak Quantum Conjecture

Andris Ambainis* Harry Buhrman† Koen Leijnse‡ Subhasree Patro§
Florian Speelman¶

July 25, 2022

arXiv:2207.11068v1 [cs.CC] 22 Jul 2022

Abstract

Classically, for many computational problems one can conclude time lower bounds conditioned on the hardness of one or more of key problems, such as k-SAT, 3SUM and APSP. More recently, similar results have been derived in the quantum setting conditioned on the quantum hardness of k-SAT and 3SUM [ACL+20, BLPS22a, BPS21]. This is done using fine-grained reductions, where the approach is to (1) select a key problem X that for some function T, is conjectured to not be solvable by any $O(T(n)^{1-\epsilon})$ time algorithm for any constant $\epsilon > 0$ (in a fixed model of computation), and (2) reduce X in a fine-grained way to these computational problems, thus giving (mostly) tight conditional time lower bounds for them.

Interestingly, for Δ-Matching Triangles and Triangle Collection, two graph problems with natural definitions, classical hardness results have been derived [AWY18] conditioned on hardness of all three key problems. More precisely, it is proven that an $O(n^{3-\epsilon})$ time classical algorithm (for any constant $\epsilon > 0$) for either of these two graph problems would imply faster classical algorithms for k-SAT, 3SUM and APSP, which makes Δ-Matching Triangles and Triangle Collection worthwhile to study.

In this paper, analogous to the classical result, we show that an $O(n^{1.5-\epsilon})$ time quantum algorithm (for any constant $\epsilon > 0$) for either of these two graph problems would imply faster quantum algorithms for k-SAT, 3SUM and APSP. To prove these results, we first formulate a quantum hardness conjecture for APSP analogous to the classical one and then present quantum reductions from k-SAT, 3SUM and APSP to Δ-Matching Triangles and Triangle Collection. Additionally, based on the quantum APSP conjecture, we are also able to prove quantum lower bounds for a matrix problem and many graph problems. The matching upper bounds follow trivially for most of them, except for Δ-Matching Triangles and Triangle Collection for which we present quantum algorithms that require careful use of data structures and Ambainis' variable time search [Amb10] as a subroutine.

Contents

1 Introduction **1**
1.1 A Weak Quantum Conjecture 1
1.2 Quantum Upper Bounds for Δ-Matching Triangles and Triangle Collection . . . 3
1.3 Related Work 4
1.4 Structure of the Paper 5

2 Preliminaries **5**

*Center for Quantum Computer Science, Faculty of Computing, University of Latvia, Latvia. andris.ambainis@lu.lv
†QuSoft, CWI and University of Amsterdam. harry.buhrman@cwi.nl
‡QuSoft, University of Amsterdam. koenleijnse@gmail.com
§QuSoft, CWI and University of Amsterdam. Subhasree.Patro@cwi.nl
¶QuSoft, CWI and University of Amsterdam. f.speelman@uva.nl