

2022–
2023



On Clifford hierarchy testing and near-extremizers of noncommutative uniformity norms

Zongbo (Bob) Bao* Jop Briët † Davi Castro-Silva ‡
Philippe van Dordrecht § Jonas Helsen¶

May 27, 2026

arXiv:2605.26983v1 [quant-ph] 26 May 2026

Abstract

We consider the problem of testing whether an unknown unitary is close to a specified level of the Clifford hierarchy. Bu, Gu, and Jaffe proposed a candidate tester for this task based on a connection with noncommutative analogues of the Gowers uniformity norms. The complexity of this tester—whose analysis depends on a robust characterization of the near-extremizers of these norms—was left open. We establish such a characterization for the fourth noncommutative uniformity norm and, as a consequence, obtain an efficient tester for the third level of the Clifford hierarchy. We further discuss possible routes toward resolving the problem of testing for all higher levels, highlighting the main barriers that remain.

1 Introduction

The challenge of manipulating quantum information in the presence of noise led to the development of quantum error-correcting codes. The task of performing gates on data encoded in such error correction codes, while controlling the propagation of errors, lies at the heart of quantum fault tolerance. Stabilizer codes are the most widely used class of quantum error-correcting codes, because of their close connection to classical linear codes and relative ease of manipulation. In these codes the so-called Clifford gates can in many cases be implemented fault-tolerantly. However, Clifford operations alone are insufficient for universal quantum computation, being classically simulable by the Gottesman–Knill theorem. Gottesman and Chuang addressed this limitation through gate teleportation, a framework that enables non-Clifford operations using only Clifford gates together with special resource states known as magic states [GC99]. In the same work, they introduced the *Clifford hierarchy*, a nested sequence of gate sets that captures the operations implementable in this framework.

Since then, the Clifford hierarchy has been studied extensively, and has found numerous applications in quantum computation and the design of fault-tolerant protocols [BK13, WSN25, HLC25, XW26, MMTE26]. Moreover, its algebraic structure has been a topic of substantial study [And24, CdS24, CGK17, dS21, GC99, HRT24, PRTC20, RCP19, ZCC08, ZLC00]. However, many fundamental questions about this algebraic structure remain unresolved.

*Centrum Wiskunde & Informatica (CWI) and QuSoft, Amsterdam, zongbo.bao@cwi.nl
†Centrum Wiskunde & Informatica (CWI) and QuSoft, Amsterdam, and Leiden University j.briet@cwi.nl
‡University of Cambridge, Cambridge, dd654@cam.ac.uk
§Centrum Wiskunde & Informatica (CWI) and QuSoft, Amsterdam, Philippe.Dordrecht@cwi.nl
¶Centrum Wiskunde & Informatica (CWI) and QuSoft, Amsterdam, jonas@cwi.nl