

From Wavefunction Regularity to Eigenvector Conditioning: Accuracy–Cost Trade-offs of Quantum Algorithms for Non-Hermitian Transcorrelated Hamiltonians

Cheng-Lin Hong,[1,2] Emiel Koridon,[3,4] Paul K. Faehrmann,[5,6]
Thomas D. Kühne,[1,2,7] Stefano Polla,[8,3] and Werner Dobrautz[1,2,9,10]

[1] *Center for Advanced Systems Understanding (CASUS), 02826 Görlitz, Germany*

[2] *Helmholtz-Zentrum Dresden-Rossendorf (HZDR), 01328 Dresden, Germany*

[3] *$\langle aQa^L \rangle$ Applied Quantum Algorithms, Leiden University, the Netherlands*

[4] *Covestro Deutschland AG, Leverkusen, Nordrhein-Westfalen 51373, Germany*

[5] *Dahlem Center for Complex Quantum Systems, Freie Universität Berlin, 14195 Berlin, Germany*

[6] *Walrus Computing, Munich, Germany*

[7] *Institute of Artificial Intelligence, Technische Universität Dresden, Helmholtzstraße 10, 01069 Dresden, Germany*

[8] *QuSoft, HIMS & IvI, University of Amsterdam, the Netherlands*

[9] *Center for Scalable Data Analytics and Artificial Intelligence (ScaDS.AI) Dresden/Leipzig, 01069 Dresden, Germany*

[10] *Technical University Dresden, 01069 Dresden, Germany*

(Dated: October 1, 2026)

arXiv:2609.39452v1 [quant-ph] 30 Sep 2026