

2015–
2019

Switch chain mixing times through triangle counts

Tom Bannink[1], Remco van der Hofstad[2] and Clara Stegehuis[2]

[1] *QuSoft and CWI, Amsterdam, The Netherlands*
[2] *Eindhoven University of Technology, Department of Mathematics and Computer Science, Eindhoven, The Netherlands*

arXiv:1711.06137v1 [math.PR] 16 Nov 2017

PACS 89.75.Hc – Networks and genealogical trees
PACS 89.75.-k – Complex systems

Abstract – Sampling uniform simple graphs with power-law degree distributions with degree exponent $\tau \in (2,3)$ is a non-trivial problem. We propose a method to sample uniform simple graphs that uses a constrained version of the configuration model together with a Markov Chain switching method. We test the convergence of this algorithm numerically in the context of the presence of small subgraphs. We then compare the number of triangles in uniform random graphs with the number of triangles in the erased configuration model. Using simulations and heuristic arguments, we conjecture that the number of triangles in the erased configuration model is larger than the number of triangles in the uniform random graph, provided that the graph is sufficiently large.

Introduction. – Many real-world networks have been found to have a power-law degree distribution with exponent $\tau \in (2,3)$ [1–3]. A uniform random graph with prescribed degrees serves as a null model for real-world networks, and has attracted enormous attention in network physics [4–6]. The uniform random graph (URG) is a uniform sample from the ensemble of all possible graphs with the prescribed degree sequence. The configuration model is used frequently to generate URGs [7]. The configuration model starts with n vertices and a degree sequence $(d_i)_{i=1,\dots,n}$ such that the sum of the degrees is even. All vertices i start with d_i half-edges, where d_i is the degree of vertex i. Then, these half-edges are paired one by one, uniformly at random. This creates a random graph with the desired degree distribution. When the configuration model results in a simple graph, this is a uniform sample of all simple graphs with that degree sequence. As long as the degree exponent τ satisfies $\tau > 3$, the probability that the configuration model creates a simple graph is strictly positive. Thus, in this regime, the configuration model can be effectively repeated until it results in a simple graph. When $\tau < 3$, the probability that the configuration model results in a simple graph vanishes instead. Thus, the configuration model cannot be used to generate uniform simple graphs for $\tau \in (2,3)$.

Several models exist to generate graphs with *approximately* the desired degree sequence [8]. One such model is the erased configuration model (ECM), where after the construction of the configuration model, all self-loops and multiple edges are removed. Another option is to use models with soft constraints on the degrees, such as hidden-variable models [9,10]. Other methods to sample uniform graphs are based on maximizing entropy [11].

A method to sample random graphs with *exactly* the desired degree sequence is to use Markov Chains. These methods start with an initial graph with the desired degree sequence. Then, at every time step, some edges of the graph are rewired in such a way that the stationary distribution is uniform [12–15]. When the number of rewirings (or *switches*) tends to infinity, the result is a uniformly sampled random graph from all simple graphs with the same degree sequence. These Markov Chain methods can be adapted to generate directed graphs [16,17], connected graphs [18] or graphs with fixed degree-degree correlations [17].

There are several ways of creating an initial graph with the desired degree sequence, one of which is by using the classical Havel-Hakimi algorithm. We introduce a new algorithm that uses a constrained version of the configuration model where self-loops and multiple edges are avoided. We experimentally study the effect of the choice of initial graph on the number of switches needed to reach equilibrium. We show that the new algorithm does not let the Markov Chain produce uniform random graphs any faster than the Havel-Hakimi algorithm.

We analyze the influence of the starting configuration