

2018–
2020

Incorporating Weisfeiler–Leman into algorithms for group isomorphism

Peter A. Brooksbank* Joshua A. Grochow† Yinan Li‡ Youming Qiao§
James B. Wilson¶

May 8, 2019

arXiv:1905.02518v1 [cs.CC] 6 May 2019

Abstract

In this paper we combine many of the standard and more recent algebraic techniques for testing isomorphism of finite groups (GpI) with combinatorial techniques that have typically been applied to Graph Isomorphism. We show how to combine several state-of-the-art GpI algorithms for specific group classes into an algorithm for general GpI, namely: composition series isomorphism (Rosenbaum–Wagner, *Theoret. Comp. Sci.*, 2015; Luks, 2015), recursively-refineable filters (Wilson, *J. Group Theory*, 2013), and low-genus GpI (Brooksbank–Maglione–Wilson, *J. Algebra*, 2017). Recursively-refineable filters—a generalization of subgroup series—form the skeleton of this framework, and we refine our filter by building a hypergraph encoding low-genus quotients, to which we then apply a hypergraph variant of the k-dimensional Weisfeiler–Leman technique. Our technique is flexible enough to readily incorporate additional hypergraph invariants or additional characteristic subgroups as they emerge.

After introducing this general technique, we prove three main results about its complexity:

- Let the *width* of a filter be the dimension of the largest quotient of two adjacent subgroups of the filter; the *color-ratio* of our hypergraph captures how much smaller a color class is compared to the layer of the filter it is coloring. When we use genus-g quotients and hypergraph k-WL, we can solve isomorphism for solvable groups of order n in time

$$\left(\frac{n}{\text{color-ratio}}\right)^{\text{width}} \text{poly}(n) + n^{O(gk)}$$

  In the "base case", where the solvable radical is itself low-genus and the semisimple part acts trivially, we can get a better guaranteed running time of $n^{O(\log\log n)}$, by combining cohomological techniques (Grochow–Qiao, CCC '14, *SIAM J. Comput.*, 2017), code equivalence (Babai–Codenotti–Grochow–Qiao, SODA '11), and low-genus isomorphism ([BMW], *ibid.*).
- We introduce a new random model of finite groups. Unlike previous models, we prove that our model has good coverage, in that it produces a wide variety of groups, and in particular a number of distinct isomorphism types that is logarithmically equivalent to the number of all isomorphism types. In this random model, we show that our filter-and-1-WL refinement method results in constant *average* width (the above result uses max width).
- For p-groups of class 2 and exponent p—widely believed to be the hardest cases of GpI, and where we also expect the above techniques to get stuck—we improve on the average-case algorithm of Li–Qiao (FOCS '17). Our new algorithm is simpler and applies to a larger fraction of random p-groups of class 2 and exponent p. The previous algorithm was based on a linear-algebraic analogue of the individualize-and-refine technique; our new algorithm combines that technique with concepts from isomorphism of low-genus groups. We also implement this algorithm in MAGMA and show that in experiments it improves over the default (brute force) algorithm for this problem.

*Department of Mathematics, Bucknell University, Lewisburg, PA 17837, United States. pbrooksb@bucknell.edu

†Departments of Computer Science and Mathematics, University of Colorado—Boulder, Boulder, CO 80309-0430, United States. jgrochow@colorado.edu

‡CWI and QuSoft, Science Park 123, 1098XG Amsterdam, Netherlands. Yinan.Li@cwi.nl.

§Center for Quantum Software and Information, University of Technology Sydney, Ultimo NSW 2007, Australia. Youming.Qiao@uts.edu.au

¶Department of Mathematics, Colorado State University, Fort Collins, CO 80523, United States. James.Wilson@ColoState.Edu