

2018–
2020

A Quantum-inspired Classical Algorithm for Separable Non-negative Matrix Factorization

Zhihuai Chen[1,2], Yinan Li[3], Xiaoming Sun[1,2], Pei Yuan[1,2], and Jialin Zhang[1,2]

[1]CAS Key Lab of Network Data Science and Technology, Institute of Computing Technology, Chinese Academy of Sciences, 100190, Beijing, China
[2]University of Chinese Academy of Sciences, 100049, Beijing, China
[3]Centrum Wiskunde & Informatica and QuSoft, Science Park 123, 1098XG Amsterdam, Netherlands
{chenzhihuai,sunxiaoming,yuanpei}@ict.ac.cn,yinan.li@cwi.nl

arXiv:1907.05568v1 [cs.DS] 12 Jul 2019

Abstract. Non-negative Matrix Factorization (NMF) asks to decompose a (entry-wise) non-negative matrix into the product of two smaller-sized nonnegative matrices, which has been shown intractable in general. In order to overcome this issue, separability assumption is introduced which assumes all data points are in a conical hull. This assumption makes NMF tractable and is widely used in text analysis and image processing, but still impractical for huge-scale datasets. In this paper, inspired by recent development on dequantizing techniques, we propose a new classical algorithm for separable NMF problem. Our new algorithm runs in polynomial time in the rank and logarithmic in the size of input matrices, which achieves an exponential speedup in the low-rank setting.

1 Introduction

Non-negative Matrix Factorization (NMF) aims to approximate a non-negative data matrix $A \in \mathbb{R}_{\geq 0}^{m\times n}$ by the product of two non-negative low rank factors, *i.e.*, $A \approx WH^T$, where $W \in \mathbb{R}_{\geq 0}^{m\times k}$ is called basis matrix, $H \in \mathbb{R}_{\geq 0}^{n\times k}$ is called encoding matrix and $k \ll \min\{m,n\}$. In many applications, an NMF often results in more natural and interpretable part-based decomposition of data [LS99]. Therefore, NMF has been widely used in a number of practical applications, such as topic modeling in text, signal separation, social network, collaborative filtering, dimension reduction, sparse coding, feature selection and hyperspectral image analysis. Since computing an NMF is NP-hard [Vav09], a series of heuristic algorithms have been proposed [LS01,Lin07,HD11,KP08,DLJ10,GTLST12]. All of the heuristic algorithms aim to minimize the reconstruction error, the formula which is a non-convex program and lack optimality guarantee:

$$\min_{W\in\mathbb{R}_{\geq 0}^{m\times k} H\in\mathbb{R}_{\geq 0}^{n\times k}} \left\|A - WH^T\right\|_F .$$

A natural assumption on the data called *separability assumption*, was observed in [DS04] . From a geometry perspective, the separable assumption means that all rows of A reside in a cone generated by a rather smaller number of rows. In particular, these generators are called anchors of A. To solve the Separable Non-Negative Matrix Factorizations (SNMF), it is sufficient to identify the anchors in the input matrices, which can be solved in polynomial time [AGKM12, AGM12, GV14, EMO$^+$12, ESV12, ZBT13, ZBG14]. Separability assumption is favored by various practical applications. For example, in the unmixing task in hyperspectral imaging, separability implies the existence of 'pure' pixel [GV14]. And in the topic detection task, it also means some words are associated with unique topic [Hof17]. In huge datasets, it is useful to pick up some representative data points to stand for other points. Such 'self-expression' assumption helps to improve the data analysis procedure [MD09, EV09].

1.1 Related work

It is natural to assume all the rows of the input A has unit ℓ_1-norm, since ℓ_1-normalization translates the conical hull to convex hull while keeping the anchors unchanged. From this perspective, most algorithms essentially identify the extreme points in the convex hull of the (ℓ_1-normalized) data vectors. In [AGKM12], the authors use m linear programs in $O(m)$ variables to identify the anchors out of m data points, and it is therefore not suitable for dealing with large-scale real-world problems. Furthermore, [RRTB12] presents a single LP in n^2 variables for SNMF to deal with large-scale problems (but is still impractical for huge-scale problems).