

2015–
2019

Finding Angles for Quantum Signal Processing with Machine Precision

Rui Chao[1,4], Dawei Ding[1,3], András Gilyén[5,6], Cupjin Huang*[1,2], and Mario Szegedy[1]

[1] *Alibaba Quantum Laboratory, Alibaba Group, Bellevue, WA, USA*
[2] *Department of Computer Science, University of Michigan, Ann Arbor, MI, USA*
[3] *Stanford Institute for Theoretical Physics, Stanford University, Stanford, CA, USA*
[4] *Department of Electrical Engineering, University of Southern California, Los Angeles, CA, USA*
[5] *QuSoft, CWI, Science Park 123 Amsterdam, The Netherlands*
[6] *Institute for Quantum Information and Matter, California Institute of Technology, Pasadena, USA*

arXiv:2003.02831v2 [quant-ph] 8 Mar 2020

Abstract

We describe an algorithm for finding angle sequences in quantum signal processing, with a novel component we call *halving* based on a new algebraic uniqueness theorem, and another we call *capitalization*. We present both theoretical and experimental results that demonstrate the performance of the new algorithm. In particular, these two algorithmic ideas allow us to find sequences of more than 3000 angles within 5 minutes for important applications such as Hamiltonian simulation, all in standard double precision arithmetic. This is native to almost all hardware.

1 Introduction

Many recent works in quantum computation consider the problem of transforming the spectrum of an unknown unitary in a black box manner. In a sequence of works [BCK15, CKS17, vAGGdW17, LC19, LC17a, CGJ19, GSLW19] an entire mathematical machinery was developed to address this problem. In particular, an elegant novel paradigm called *quantum signal processing* was introduced by [LYC16], which was later organically combined with *qubitization* [LC19, LC17a] in order to address the problem in great generality. Quantum signal processing implements polynomial transformations in a very efficient way using only one ancilla qubit with the help of a sequence of single qubit rotation gates. In [GSLW19] these techniques were further developed, leading to a Quantum Singular Value Transformation (QSVT) algorithm, with applications ranging from oblivious amplitude amplification to Gibbs sampling and Hamiltonian simulation. However, finding a sequence of angles for the rotation gates corresponding to a desired transformation can be a challenging (classical) task [CMN+18]. In order to demonstrate the practicality of quantum algorithms based on quantum signal processing, it is important to show that there is an efficient classical algorithm to find the angles. This question was addressed by [Haa19], where they showed that this is indeed the case and that the problem can be elegantly treated by considering Laurent polynomials, that is, polynomials with both positive and negative powers.

The main result of our paper can be best summarized as a new algorithm for finding these angles, which shows surprising numerical stability. Specifically, our paper presents novel contributions to this field in two ways:

*cupjin.huang@alibaba-inc.com