


Attacks on the AJPS Mersenne-based Cryptosystem

Koen de Boer[1], Léo Ducas[1], Stacey Jeffery[1,2], and Ronald de Wolf[1,2,3]

[1] CWI, Amsterdam
[2] QuSoft
[3] University of Amsterdam

Abstract. Aggarwal, Joux, Prakash and Santha recently introduced a new potentially quantum-safe public-key cryptosystem, and suggested that a brute-force attack is essentially optimal against it. They consider but then dismiss both Meet-in-the-Middle attacks and LLL-based attacks. Very soon after their paper appeared, Beunardeau et al. proposed a practical LLL-based technique that seemed to significantly reduce the security of the AJPS system. In this paper we do two things. First, we show that a Meet-in-the-Middle attack can also be made to work against the AJPS system, using locality-sensitive hashing to overcome the difficulty that Aggarwal et al. saw for such attacks. We also present a quantum version of this attack. Second, we give a more precise analysis of the attack of Beunardeau et al., confirming and refining their results.

1 Introduction

Aggarwal, Joux, Prakash and Santha [1] recently proposed a variant of the NTRU public-key encryption scheme [13]. This variant uses integers with sparse binary representation as a secret key, rather than polynomials with small coefficients. In particular, their cryptosystem is suspected to be resistant to quantum attacks.

Their system works as follows. Consider a *Mersenne* number $N = 2^n - 1$, with n prime. Then we can identify the ring $R = \mathbb{Z}/N\mathbb{Z}$ with the set of n-bit strings, where 1^n is identified with 0^n. To set up the keys of the cryptosystem, choose $f, g \in R$ of fixed Hamming weight $w = \lfloor \sqrt{n}/2 \rfloor$ uniformly at random, subject to g having a multiplicative inverse in R. Set the *public* key to $h := f/g$ (this corresponds to an n-bit string of arbitrary Hamming weight) and the *private* key to g. In the next section we describe how Aggarwal et al. use these keys for encryption and decryption.

The security of this system relies on the assumption that it is hard to solve the following *Mersenne Low Hamming Ratio Search Problem*: given $n, w \in \mathbb{N}$ and $h \in R$, find $f, g \in R$ of weight w such that $h = f/g$, assuming such f and g exist. A brute-force attack on this system would just try out all $\binom{n-1}{w-1}$ possible g's of weight w that start with a 1 (the latter is without loss of generality) and check whether hg has weight w. Aggarwal et al. [1] suggest that this brute-force attack is close to optimal. This would correspond to roughly $\lambda = \log \binom{n-1}{w-1} \approx \frac{1}{2} \cdot w \log n$ bits of security. On a quantum computer, this brute-force attack could