

Non-interactive Cryptographic Timestamping based on Verifiable Delay Functions

Esteban Landerreche[1], Marc Stevens[1], and Christian Schaffner[2]

[1] CWI Amsterdam
[2] University of Amsterdam & QuSoft

esteban@cwi.nl

Abstract. We present the first treatment of non-interactive publicly-verifiable timestamping schemes in the Universal Composability framework. Similar to a simple construction by Mahmoody et al., we use non-parallelizable computational work that relates to elapsed time to avoid previous impossibility results on non-interactive timestamping. We extend these ideas to the UC-framework and show how to model verifiable delay functions (VDF) related to a global clock, and non-interactive timestamping, in the UC-framework. Furthermore, we present new constructions that are substantial improvements over Mahmoody et al.'s construction, such that any forged timestamps by the adversary are now limited to within a certain time-window that depends only on its ratio to compute VDFs more quickly and the time-window of corruption. Finally, we discuss natural applications for our construction in decentralized protocols.

Keywords: non-interactive cryptographic timestamping, universal composability, verifiable delay functions, time-lock cryptography

1 Introduction

In the digital domain, giving evidence that a certain amount of time has passed is more challenging than in the physical world. Exploring how to reliably create digital timestamps has been an active research area for the last thirty years. The first paper to deal with digital timestamping by Haber and Stornetta [HS91] presented two different solutions that avoid having to fully trust a third party to validate timestamps. Their first solution uses a hashchain: a sequence of documents linked through a collision-resistant hash function. The second solution relies on a pseudorandom function to choose a set of validators for a timestamp, which also allows to identify misbehaving actors. Both solutions require interaction with distributed validators, as a different hashchain can be easily generated by an adversarial party.

Modifications and extensions of these protocols have been proposed, most notably substituting the individual records in a hashchain with a Merkle tree (or similar) [BHS93, BLS00]. These timestamping systems require many parties to maintain records and their timestamps, as well as the availability to answer validation queries. Other protocols require less space but stronger trust assumptions on the set of validators [BDM93].

While timestamping evokes the idea of fixing an event in a specific point in clocktime, in practice most timestamping schemes are relative; they provide only an ordering. A significant limitation of such ordering systems is that it is impossible to directly compare the timestamps to events outside the protocol. Clock-based timestamping generally requires stronger trust assumptions, as the notion of clocktime in a computational setting is problematic.

One of the goals of this paper is to provide the first treatment of non-interactive timestamping in the universal composability framework. In the classical literature, almost every timestamping service requires interaction with a group of validators and provides security guarantees only for relative timestamping. Non-interactive timestamping has been explored before in [MSTS04], where the authors present a generic impossibility result, as an adversarial prover would simply need to simulate the execution of an honest prover to generate a fake timestamp. They sidestep this result by working in the bounded-storage model where they construct a secure protocol. Another approach to sidestep this result is to relate computational work to elapsed time.