

2019–
2024

Breaking the decisional Diffie-Hellman problem for class group actions using genus theory – extended version

Wouter Castryck[1], Jana Sotáková[2], and Frederik Vercauteren[1]

wouter.castryck@esat.kuleuven.be, j.s.sotakova@uva.nl,
frederik.vercauteren@esat.kuleuven.be

[1] imec-COSIC, KU Leuven, Belgium
[2] QuSoft/University of Amsterdam, The Netherlands

Abstract. In this paper, we use genus theory to analyze the hardness of the decisional Diffie–Hellman problem for ideal class groups of imaginary quadratic orders acting on sets of elliptic curves through isogenies (DDH-CGA). Such actions are used in the Couveignes–Rostovtsev–Stolbunov protocol and in CSIDH. Concretely, genus theory equips every imaginary quadratic order $\mathcal{O}$ with a set of assigned characters $\chi : \mathrm{cl}(\mathcal{O}) \to \{\pm 1\}$, and for each such character and every secret ideal class $[\mathfrak{a}]$ connecting two public elliptic curves E and $E' = [\mathfrak{a}] \star E$, we show how to compute $\chi([\mathfrak{a}])$ given only E and E', i.e. without knowledge of $[\mathfrak{a}]$. In practice, this breaks DDH-CGA as soon as the class number is even, which is true for a density 1 subset of all imaginary quadratic orders. For instance, our attack works very efficiently for all supersingular elliptic curves over $\mathbb{F}_p$ with $p \equiv 1 \bmod 4$. Our method relies on computing Tate pairings and walking down isogeny volcanoes. We also show that these ideas carry over, at least partly, to abelian varieties of arbitrary dimension. This is an extended version of the paper that was presented at Crypto 2020.

Keywords: Decisional Diffie-Hellman, isogeny-based cryptography, class group action, CSIDH.

1 Introduction

"The Decision Diffie–Hellman assumption (DDH) is a gold mine", Dan Boneh wrote in his 1998 overview paper [3]. This statement still holds true (maybe even more so), since DDH is fundamental to prove security of many widely used protocols such as Diffie–Hellman key agreement [27], El Gamal encryption [31], but

* This work was supported in part by the European Research Council (ERC) under the European Union's Horizon 2020 research and innovation programme (grant agreement ISOCRYPT - No. 101020788) and by the Research Council KU Leuven grants C14/18/067, and by CyberSecurity Research Flanders with reference number VR20192203. JS was supported by the Dutch Research Council (NWO) through Gravitation-grant Quantum Software Consortium - 024.003.037.