

2019–
2024

Explicit connections between supersingular isogeny graphs and Bruhat–Tits trees

Laia Amorós,[1] Annamaria Iezzi,[2,3] Kristin Lauter,[4]
Chloe Martindale,[5] and Jana Sotáková[6,7]*

[1]Aalto University, [2]University of South Florida, [3]Université de la Polynésie Française,
[4]Microsoft Research, [5]University of Bristol, [6]QuSoft, [7]University of Amsterdam

laia.ac@protonmail.com, annamaria.iezzi@gmail.com, kristinelauter@gmail.com,
chloe.martindale@bristol.ac.uk, ja.sotakova@gmail.com

March 19, 2021

Abstract

We give an exposition of supersingular isogeny graphs, quaternion ideal graphs and Bruhat–Tits trees, and of their connections. Bruhat–Tits trees are combinatorial objects whose vertices and edges have a very simple representation as two-by-two matrices, which, as we show, is useful for understanding certain aspects of the corresponding elliptic curves and isogenies. Moreover Bruhat–Tits trees can be given an orientation and a notion of depth that we translate into the setting of supersingular isogeny graphs. We give some suggestions towards using Bruhat–Tits trees as a tool for cryptanalysis of certain cryptosystems based on supersingular isogeny graphs.

1 Introduction

Post-Quantum Cryptography (PQC) is a subfield of cryptography that focuses on cryptosystems designed to withstand an attacker who has access to a quantum computer. An emerging field in post-quantum cryptography is isogeny-based cryptography, which is based on the hardness of computing a large-degree isogeny between two given elliptic curves. Most practical proposals in the area restrict to isogenies of supersingular elliptic curves, which were introduced into cryptography by Charles, Goren and Lauter [CGL09a] (first published in 2006 [CGL06]) for constructing cryptographic hash functions. Later, Jao and De Feo [JF11] proposed a Diffie–Hellman style key exchange based on supersingular isogenies called SIDH, or *Supersingular Isogeny Diffie–Hellman*. Post-quantum cryptography has enjoyed an increase in interest since the advent of the NIST international 'competition' [NIST], initiated in 2016, to find a post-quantum cryptographic standard. The only isogeny-based submission in the NIST competition is the key encapsulation mechanism SIKE [SIKE], or *Supersingular Isogeny Key Encapsulation*, which is based on SIDH. To assure the long-term security of schemes for future use in widely deployed cryptosystems, we need more research on the hardness of computing isogenies in supersingular

*Authors in alphabetical order; `https://www.ams.org/profession/leaders/culture/CultureStatement04.pdf`.