





2016–
2022

Quantum Fully Homomorphic Encryption With Verification

Gorjan Alagic[1,2], Yfke Dulek[3], Christian Schaffner[3], and Florian Speelman[4]

[1] Joint Center for Quantum Information and Computer Science, University of Maryland, College Park, MD
[2] National Institute of Standards and Technology, Gaithersburg, MD
[3] CWI, QuSoft, and University of Amsterdam
[4] QMATH, Department of Mathematical Sciences, University of Copenhagen

arXiv:1708.09156v1 [quant-ph] 30 Aug 2017

Abstract. Fully-homomorphic encryption (FHE) enables computation on encrypted data while maintaining secrecy. Recent research has shown that such schemes exist even for quantum computation. Given the numerous applications of classical FHE (zero-knowledge proofs, secure two-party computation, obfuscation, etc.) it is reasonable to hope that quantum FHE (or QFHE) will lead to many new results in the quantum setting. However, a crucial ingredient in almost all applications of FHE is *circuit verification*. Classically, verification is performed by checking a transcript of the homomorphic computation. Quantumly, this strategy is impossible due to no-cloning. This leads to an important open question: can quantum computations be delegated and verified in a non-interactive manner?
In this work, we answer this question in the affirmative, by constructing a scheme for QFHE with verification (vQFHE). Our scheme provides authenticated encryption, and enables arbitrary polynomial-time quantum computations without the need of interaction between client and server. Verification is almost entirely classical; for computations that start and end with classical states, it is completely classical. As a first application, we show how to construct quantum one-time programs from classical one-time programs and vQFHE.

1 Introduction

The 2009 discovery of fully-homomorphic encryption (FHE) in classical cryptography is widely considered to be one of the major breakthroughs of the field. Unlike standard encryption, FHE enables non-interactive computation on encrypted data even by parties that do not hold the decryption key. Crucially, the input, output, and all intermediate states of the computation remain encrypted, and thus hidden from the computing party. While FHE has some obvious applications (e.g., cloud computing), its importance in cryptography stems from its wide-ranging applications to other cryptographic scenarios. For instance, FHE can be used to construct secure two-party computation, efficient zero-knowledge proofs for NP, and indistinguishability obfuscation [4, 14]. In fact, the breadth of its usefulness has led some to dub FHE "the swiss army knife of cryptography"[4].

Recent progress on constructing quantum computers has led to theoretical research on "cloud-based" quantum computing. In such a setting, it is natural to ask whether users can keep their data secret from the server that performs the quantum computation. A recently-constructed quantum fully-homomorphic encryption (QFHE) scheme shows that this can be done in a single round of interaction [12]. This discovery raises an important question: do the numerous classical applications of FHE have suitable quantum analogues? As it turns out, most of the classical applications require an additional property which is simple classically, but non-trivial quantumly. That property is *verification*: the ability of the user to check that the final ciphertext produced by the server is indeed the result of a particular computation, homomorphically applied to the initial user-generated ciphertext. In the classical case, this is a simple matter: the server makes a copy of each intermediate computation step, and provides the user with all these copies. In the quantum case, such a "transcript" would appear to violate no-cloning. the user simply checks a transcript generated by the server. In the quantum case, this would violate no-cloning. In fact, one might suspect that the no-cloning theorem prevents non-interactive quantum verification *in principle*.

In this work, we show that verification of homomorphic quantum computations is in fact possible. We construct a new QFHE scheme which allows the server to generate a "computation log" which can certify