

2016–
2022

Simon's problem for linear functions

Joran van Apeldoorn* Sander Gribling*

arXiv:1810.12030v2 [quant-ph] 3 Jan 2019

Abstract

Simon's problem asks the following: determine if a function $f : \{0,1\}^n \to \{0,1\}^n$ is one-to-one or if there exists a unique $s \in \{0,1\}^n$ such that $f(x) = f(x \oplus s)$ for all $x \in \{0,1\}^n$, given the promise that exactly one of the two holds. A classical algorithm that can solve this problem for every f requires $2^{\Omega(n)}$ queries to f. Simon [Sim97] showed that there is a quantum algorithm that can solve this promise problem for every f using only $\mathcal{O}(n)$ quantum queries to f. A matching lower bound on the number of quantum queries was given in [KNP07], even for functions $f : \mathbb{F}_p^n \to \mathbb{F}_p^n$. We give a short proof that $\mathcal{O}(n)$ quantum queries is optimal even when we are additionally promised that f is linear. This is somewhat surprising because for linear functions there even exists a *classical* n-query algorithm.

1 Introduction

In 1994, Simon [Sim97] showed the existence of a query problem where quantum algorithms offer an exponential improvement over the best randomized classical algorithms that have a bounded error probability of, say, at most 1/3. The problem he considers is the following:

Given a function $f : \{0,1\}^n \to \{0,1\}^n$ with the promise that it either (1) is one-to-one or (2) admits a unique $s \in \{0,1\}^n$ such that $f(x) = f(x \oplus s)$ for all $x \in \{0,1\}^n$, decide which of the two holds.

Simon showed that there is a quantum algorithm which can solve this promise problem for any f using $\mathcal{O}(n)$ quantum queries to f, i.e., using $\mathcal{O}(n)$ applications of the unitary $|x\rangle|b\rangle \mapsto |x\rangle|b \oplus f(x)\rangle$.[1] This offers an exponential improvement over classical algorithms, since Simon also showed that at least $2^{\Omega(n)}$ classical queries of the form $x \mapsto f(x)$ are needed in order to succeed with probability at least 2/3. The question we are interested in is the optimality of Simon's quantum algorithm and its generalization to finite fields. Let p be a prime power and let $\mathbb{F}_p$ be the finite field with p elements. Simon's problem over $\mathbb{F}_p$ can be formulated as follows:

Given a function $f : \mathbb{F}_p^n \to \mathbb{F}_p^n$ with the promise that it either (1) is one-to-one or (2) admits a one-dimensional subspace $H \subset \mathbb{F}_p^n$ such that for all $x, y \in \mathbb{F}_p^n$, $f(x) = f(y) \Leftrightarrow x - y \in H$, decide which of the two holds.

Koiran et al. [KNP07] (for an earlier version see [KNP05]) showed that the quantum query complexity of Simon's problem over $\mathbb{F}_p$ is $\Theta(n)$.[2] Here we show that the lower bound of $\Omega(n)$ quantum queries holds even when f is additionally promised to be linear. That is, a quantum algorithm which can solve Simon's problem over $\mathbb{F}_p$ for any linear function requires $\Omega(n)$ quantum queries to f. Interestingly, this shows that for the class of linear functions there is no quantum advantage: classically, one can also fully determine a linear function using n queries, by querying a basis.

*QuSoft, CWI, the Netherlands. Both authors are supported by the Netherlands Organization for Scientific Research, grant number 617.001.351. The first author is also partially supported by QuantERA, project QuantAlgo 680-91-034. {apeldoor,gribling}@cwi.nl

[1] In fact, Simon considered the problem of finding the non-zero string s, if it exists. Here we focus on the decision version of his problem. However, all upper bounds mentioned are derived from algorithms which also find s.

[2] They even prove the analogous lower bound for the hidden subgroup problem over Abelian groups, see Section 3.