arXiv:1901.04921v1 [quant-ph] 15 Jan 2019

Semidefinite programming formulations for the completely bounded norm of a tensor

Sander Gribling* Monique Laurent†

Abstract

We show that a certain tensor norm, the *completely bounded norm*, can be expressed by a semidefinite program. This tensor norm recently attracted attention in the field of quantum computing, where it was used by Arunachalam, Briët and Palazuelos for characterizing the quantum query complexity of Boolean functions. Combined with their results, we obtain a new characterization of the quantum query complexity through semidefinite programming. Using the duality theory of semidefinite programming we obtain a new type of certificates for large query complexity. We show that our class of certificates encompasses the linear programming certificates corresponding to the approximate degree of a Boolean function.

1 Introduction

Throughout, we let $T = (T_{i_1,\dots,i_t}) \in \mathbb{R}^{n\times\cdots\times n}$ be a t-tensor acting on $\mathbb{R}^n$. The *completely bounded norm* of T is defined as

$$||T||_{\mathrm{cb}} := \sup\Big\{ \Big|\Big| \sum_{i_1,\dots,i_t=1}^{n} T_{i_1,\dots,i_t} U_1(i_1)\cdots U_t(i_t) \Big|\Big| \ : \ d\in\mathbb{N},\ U_j(i)\in O(d) \text{ for } i\in[n], j\in[t] \Big\}. \quad (1)$$

Here $||\cdot||$ is the operator norm and $O(d)\subseteq\mathbb{R}^{d\times d}$ is the group of $d\times d$ orthogonal matrices. Note that in (1) one could equivalently optimize over *complex* unitary matrices $U_j(i)$.

We first show that $||T||_{\mathrm{cb}}$ can be expressed as the optimal value of a semidefinite program (SDP). This SDP involves matrices of size $O(n^{\lceil t/2\rceil})$ and $O(n^{2\lceil t/2\rceil})$ linear constraints, so that an additive ε-approximation of its optimal value can be obtained in time $\mathrm{poly}(n^t, \log(1/\varepsilon))$ (see Theorem 3.4 in Section 3).

To put this result in perspective, if we replace the product $U_1(i_1)\cdots U_t(i_t)$ by the Kronecker (or tensor) product $U_1(i_1)\otimes\cdots\otimes U_t(i_t)$ then we obtain the *jointly completely bounded norm* of T. It is known that there is a one-to-one correspondence between the jointly completely bounded norm of a t-tensor and the entangled bias of an associated t-partite XOR game. The latter can be computed in polynomial time when $t=2$ [Tsi87], but it is an NP-hard problem to give any constant factor multiplicative approximation of the entangled bias of a 3-partite XOR game [Vid16]. Hence the jointly completely bounded norm of a 3-tensor is hard to approximate up to any constant factor.

*Centrum Wiskunde & Informatica (CWI) and QuSoft, Amsterdam, The Netherlands. The work was supported by the Netherlands Organization for Scientific Research, grant number 617.001.351.

†Centrum Wiskunde & Informatica (CWI) and QuSoft, Amsterdam and Tilburg University, The Netherlands.