

2017–
2021



# Non-malleability for quantum public-key encryption

Christian Majenz[1], Christian Schaffner[1], and Jeroen van Wier[2]

[1]Institute for Logic, Language and Computation, University of Amsterdam & QuSoft, Amsterdam, Netherlands

[2]Interdisciplinary Centre for Security, Reliability and Trust, University of Luxembourg, Esch-sur-Alzette, Luxembourg

arXiv:1905.05490v3 [quant-ph] 26 Mar 2021

Non-malleability is an important security property for public-key encryption (PKE). Its significance is due to the fundamental unachievability of integrity and authenticity guarantees in this setting, rendering it the strongest integrity-like property achievable using only PKE, without digital signatures. In this work, we generalize this notion to the setting of *quantum* public-key encryption. Overcoming the notorious "recording barrier" known from generalizing other integrity-like security notions to quantum encryption, we generalize one of the equivalent classical definitions, comparison-based non-malleability, and show how it can be fulfilled. In addition, we explore one-time non-malleability notions for symmetric-key encryption from the literature by defining plaintext and ciphertext variants and by characterizing their relation.

## 1 Introduction

The development of quantum information processing technology has accelerated recently, with many large public and private players investing heavily [Wal18]. A future where communication networks include at least some high-capacity quantum channels and fault-tolerant quantum computers seems therefore more and more likely. How will we secure communication over the resulting "quantum internet" [WEH18]? One approach is to rely on features inherent to quantum theory to get unconditional security, e.g. by using teleportation. Such methods are, however, a far cry from the classical standard internet cryptography in terms of efficiency, as they require interaction. A different and more efficient approach is to generalize modern private- and public-key cryptography to the quantum realm.

In this paper, we focus on the notion of non-malleability, which captures the idea that an encrypted message cannot be altered by a third party in a structured manner. This notion, first introduced by Dolev, Dwork and Naor [DDN03], derives its importance from the fact that it is the strongest integrity-like notion that is achievable using public-key encryption only. The aim of this work is to generalize this notion to public-key encryption of quantum data. A recent attack that exemplifies the relevance of the concept of non-malleability is the "efail"-attack on the PGP protocol for confidential and authenticated e-mail communication [Pod+18]. This kind of attack, where an attacker is not directly able to learn the message yet still able to modify it, is exactly what non-malleable encryption secures against.

The classical notion of non-malleability is based on the notion of related plaintexts. For a non-malleable encryption scheme, it should, roughly speaking, be hard for an adversary to transform an encryption of a message $m$ into a *different* ciphertext that decrypts to a *related* message $m'$. Here, "related" just means that the adversary has some control over the transformation that is applied to the plaintext underlying the ciphertext he attacks. Generalizing this notion to the quantum case is complicated by the quantum no-cloning theorem: After a message has been encrypted and modified by the adversary and subsequently decrypted, it cannot be compared with the result anymore. In addition, it cannot be checked in a straightforward manner whether the adversary has indeed modified the ciphertext.

Christian Majenz: c.majenz@uva.nl
Christian Schaffner: c.schaffner@uva.nl
Jeroen van Wier: jeroen.vanwier@uni.lu