

Span Programs and Quantum Space Complexity

Stacey Jeffery*

CWI and QuSoft

August 30, 2019

arXiv:1908.04232v2 [quant-ph] 29 Aug 2019

Abstract

While quantum computers hold the promise of significant computational speedups, the limited size of early quantum machines motivates the study of space-bounded quantum computation. We relate the quantum space complexity of computing a function f with *one-sided error* to the logarithm of its *span program size*, a classical quantity that is well-studied in attempts to prove formula size lower bounds.

In the more natural *bounded error* model, we show that the amount of space needed for a unitary quantum algorithm to compute f with bounded (two-sided) error is lower bounded by the logarithm of its *approximate span program size*. Approximate span programs were introduced in the field of quantum algorithms but not studied classically. However, the approximate span program size of a function is a natural generalization of its span program size.

While no non-trivial lower bound is known on the span program size (or approximate span program size) of any concrete function, a number of lower bounds are known on the *monotone span program size*. We show that the approximate monotone span program size of f is a lower bound on the space needed by quantum algorithms of a particular form, called *monotone phase estimation algorithms*, to compute f. We then give the first non-trivial lower bound on the approximate span program size of an explicit function.

1 Introduction

While quantum computers hold the promise of significant speedups for a number of problems, building them is a serious technological challenge, and it is expected that early quantum computers will have quantum memories of very limited size. This motivates the theoretical question: what problems could we solve faster on a quantum computer with limited space? Or similarly, what is the minimum number of qubits needed to solve a given problem (and hopefully still get a speedup).

We take a modest step towards answering such questions, by relating the space complexity of a function f to its *span program size* (see Definition 3.3), which is a measure that has received significant attention in theoretical computer science over the past few decades. Span programs are a model of computation introduced by Karchmer and Wigderson [KW93] in an entirely classical setting; they defined the span program size of a function in order to lower bound the size of *counting branching programs*. Some time later, Reichardt and Špalek [RŠ12] related span programs to quantum algorithms, and introduced the new measure of *span program complexity* (see Definition 3.4). The importance of span programs in quantum algorithms stems from the ability to compile any span program for a function f into a bounded error quantum algorithm for f [Rei09]. In particular, there is a tight correspondence between the span program *complexity* of f, and its quantum query complexity – a rather surprising and beautiful connection for a model originally

*jeffery@cwi.nl. SJ is supported by an NWO WISE Fellowship, an NWO Veni Innovational Research Grant under project number 639.021.752, and QuantERA project QuantAlgo 680-91-03. SJ is a CIFAR Fellow in the Quantum Information Science Program.