

2016–
2022





2017–
2021





arXiv:1909.13770v2 [quant-ph] 4 May 2020

Secure Multi-party Quantum Computation with a Dishonest Majority

Yfke Dulek[1], Alex Grilo[2], Stacey Jeffery[2], Christian Majenz[2], and Christian Schaffner[1]

[1]QuSoft and University of Amsterdam, The Netherlands

[2]QuSoft and CWI, Amsterdam, The Netherlands

The cryptographic task of secure multi-party (classical) computation has received a lot of attention in the last decades. Even in the extreme case where a computation is performed between k mutually distrustful players, and security is required even for the single honest player if all other players are colluding adversaries, secure protocols are known. For quantum computation, on the other hand, protocols allowing arbitrary dishonest majority have only been proven for $k = 2$. In this work, we generalize the approach taken by Dupuis, Nielsen and Salvail (CRYPTO 2012) in the two-party setting to devise a secure, efficient protocol for multi-party quantum computation for any number of players k, and prove security against up to $k - 1$ colluding adversaries. The quantum round complexity of the protocol for computing a quantum circuit of $\{\mathsf{CNOT}, \mathsf{T}\}$ depth d is $O(k \cdot (d + \log n))$, where n is the security parameter. To achieve efficiency, we develop a novel public verification protocol for the Clifford authentication code, and a testing protocol for magic-state inputs, both using classical multi-party computation.

1 Introduction

In secure multi-party computation (MPC), two or more players want to jointly compute some publicly known function on their private data, without revealing their inputs to the other players. Since its introduction by Yao [Yao82], MPC has been extensively developed in different setups, leading to applications of both theoretical and practical interest (see, e.g., [CDN15] for a detailed overview).

With the emergence of quantum technologies, it becomes necessary to understand its consequences in the field of MPC. First, classical MPC protocols have to be secured against quantum attacks. But also, the increasing number of applications where quantum computational power is desired motivates protocols enabling multi-party *quantum* computation (MPQC) on the players' private (possibly quantum) data. In this work, we focus on the second task. Informally, we say a MPQC protocol is secure if the following two properties hold: 1. Dishonest players gain no information about the honest players' private inputs. 2. If the players do not abort the protocol, then at the end of the protocol they share a state corresponding to the correct computation applied to the inputs of honest players (those that follow the protocol) and some choice of inputs for the dishonest players.

Yfke Dulek: yfkedulek@gmail.com, This is the full version of an article published in the conference proceedings of EUROCRYPT 2020 [DGJ+20].

Alex Grilo: abgrilo@gmail.com

Stacey Jeffery: smjeffery@gmail.com

Christian Majenz: c.majenz@cwi.nl

Christian Schaffner: c.schaffner@uva.nl