

2019–
2021

Strategies for solving the Fermi-Hubbard model on near-term quantum computers

Chris Cade,[1,*] Lana Mineh,[1,2,3] Ashley Montanaro,[1,2] and Stasja Stanisic[1]

[1]*Phasecraft Ltd.*
[2]*School of Mathematics, University of Bristol*
[3]*Quantum Engineering Centre for Doctoral Training, University of Bristol*

(Dated: December 1, 2020)

The Fermi-Hubbard model is of fundamental importance in condensed-matter physics, yet is extremely challenging to solve numerically. Finding the ground state of the Hubbard model using variational methods has been predicted to be one of the first applications of near-term quantum computers. Here we carry out a detailed analysis and optimisation of the complexity of variational quantum algorithms for finding the ground state of the Hubbard model, including costs associated with mapping to a real-world hardware platform. The depth complexities we find are substantially lower than previous work. We performed extensive numerical experiments for systems with up to 12 sites. The results suggest that the variational ansätze we used – an efficient variant of the Hamiltonian Variational ansatz and a novel generalisation thereof – will be able to find the ground state of the Hubbard model with high fidelity in relatively low quantum circuit depth. Our experiments include the effect of realistic measurements and depolarising noise. If our numerical results on small lattice sizes are representative of the somewhat larger lattices accessible to near-term quantum hardware, they suggest that optimising over quantum circuits with a gate depth less than a thousand could be sufficient to solve instances of the Hubbard model beyond the capacity of classical exact diagonalisation.

arXiv:1912.06007v3 [quant-ph] 30 Nov 2020

Modelling quantum-mechanical systems is widely expected to be one of the most important applications of near-term quantum computing hardware [1–3]. Quantum computers could enable the solution of problems in the domains of many-body quantum physics and quantum chemistry that are intractable for today's best supercomputers.

Quantum algorithms have been proposed for both dynamic and static simulation of quantum systems. In the former case, one seeks to approximate time-evolution according to a certain quantum Hamiltonian. In many physically relevant cases, such as Hamiltonians obeying a locality constraint on their interactions, this can be carried out efficiently, i.e. in time polynomial in the system size [4]; by contrast, even to write down a classical description of the quantum system would take exponential time. However, in cases where the performance of the quantum simulation algorithm has been calculated and optimised in detail, solving a large enough problem instance to be practically relevant is still beyond the capabilities of present-day quantum computing technology. For example, several recent works describing highly-optimised algorithms for time-dynamics simulation [5–7] determine complexities in the range of $10^5 - 10^8$ quantum gates to simulate systems beyond classical capabilities. By comparison, the most complex quantum circuit executed in the recent demonstration by Google of a quantum computation outperforming a classical supercomputer contained 430 two-qubit gates [8].

In the case of static simulation, the canonical problem is to produce the ground state of a quantum Hamiltonian. Once this state is produced, measurements can be performed to determine its properties. Although this problem is expected to be computationally hard for quantum computers in the worst case [9], it is plausible that instances of practical importance could nevertheless be solved efficiently. A prominent class of methods for producing ground states are variational methods, and in particular the variational quantum eigensolver [10, 11] (VQE). The VQE framework can be seen as a hybrid quantum-classical approach to produce a ground state of a quantum Hamiltonian H. A classical optimiser is used to optimise over quantum circuits which produce states $|\psi\rangle$ that are intended to be the ground state of H. The cost function provided to the optimiser is an approximation of the energy $\langle\psi|H|\psi\rangle$, which is estimated using a quantum computer.

Here our focus is on variational algorithms for a specific task: constructing the ground state of the iconic 2D Fermi–Hubbard model [12, 13]. This model is of particular interest for several reasons. First, despite its apparent simplicity, its theoretical properties are far from fully understood [13–15]. Second, it is believed to be relevant to physical phenomena of extreme practical importance, such as high-temperature superconductivity [16]. Third, its regular structure and relatively simple form suggest that it may be easier to implement on a near-term quantum computer than, for example, model systems occurring in quantum chemistry.

The Hubbard Hamiltonian is defined as

$$H = -t \sum_{\langle i,j\rangle,\sigma} (a^\dagger_{i\sigma} a_{j\sigma} + a^\dagger_{j\sigma} a_{i\sigma}) + U \sum_i n_{i\uparrow} n_{i\downarrow}, \qquad (1)$$

where $a^\dagger_{i\sigma}$, $a_{i\sigma}$ are fermionic creation and annihilation operators; $n_{i\uparrow} = a^\dagger_{i\uparrow} a_{i\uparrow}$ and similarly for $n_{i\downarrow}$; the notation $\langle i,j\rangle$ in the first sum associates sites that are adjacent in an $n_x \times n_y$ rectangular lattice ("grid"); and $\sigma \in \{\uparrow,\downarrow\}$. The first term in (1) is called the hopping term with t being the tunnelling amplitude, and the second term is called the interaction or onsite term where U is the Coulomb potential. We will usually fix $t = 1, U = 2$ (similarly to [17]); see Appendix D 1 for results suggesting that the complexity of approximately finding the ground state of H is not substantially different for other U not too large and sufficiently bounded away from 0. We some-

* Present address: QuSoft and CWI, Amsterdam.