

2016–
2022



Impossibility of Quantum Virtual Black-Box Obfuscation of Classical Circuits

Gorjan Alagic* Zvika Brakerski‡ Yfke Dulek§ Christian Schaffner§

arXiv:2005.06432v2 [quant-ph] 20 Nov 2020

Abstract

Virtual black-box obfuscation is a strong cryptographic primitive: it encrypts a circuit while maintaining its full input/output functionality. A remarkable result by Barak et al. (Crypto 2001) shows that a general obfuscator that obfuscates classical circuits into classical circuits cannot exist. A promising direction that circumvents this impossibility result is to obfuscate classical circuits into quantum states, which would potentially be better capable of hiding information about the obfuscated circuit. We show that, under the assumption that Learning With Errors (LWE) is hard for quantum computers, this quantum variant of virtual black-box obfuscation of classical circuits is generally impossible. On the way, we show that under the presence of dependent classical auxiliary input, even the small class of classical point functions cannot be quantum virtual black-box obfuscated.

1 Introduction

The obfuscation of a circuit is an object, typically another circuit, that allows a user to evaluate the functionality of the original circuit without learning any additional information about the structure of the circuit. Obfuscation is useful for publishing software without revealing the code, but it also has more fundamental applications in cryptography. For example, the strongest notion called *virtual black-box* obfuscation can transform any private-key encryption scheme into a public-key scheme, and transform public-key schemes into fully-homomorphic schemes. Unfortunately, this notion turns out to be impossible for general circuits [BGI+01] – at least, if we require the obfuscation of a circuit to be a circuit itself.

The impossibility result from [BGI+01] leaves open an intriguing possibility: what if the obfuscation of a (classical) circuit is allowed to be a *quantum state*? Could a quantum state contain all the information about a functionality, allowing a user to produce correct outputs, without revealing all that information? This possibility seems hopeful, due to the unrevealing nature of quantum states. However, in this work, we show that virtual-black-box obfuscating classical circuits into quantum states is not possible.

1.1 Related work

Barak et al. defined the obfuscating property of virtual black-box (vbb) obfuscators as follows: any information that an adversary can learn about a circuit from its obfuscation can also be learned by a simulator that does not have access to the obfuscation, but only to an oracle for the circuit's

*QuICS, University of Maryland; National Institute of Standards and Technology
‡Weizmann Institute of Science, zvika.brakerski@weizmann.ac.il.
§QuSoft; University of Amsterdam, yfkedulek@gmail.com, c.schaffner@uva.nl