

2016–
2022

Device-independent quantum key distribution from computational assumptions

Tony Metger,[1,*] Yfke Dulek,[2] Andrea Coladangelo,[3] and Rotem Arnon-Friedman[4]

[1] *Institute for Theoretical Physics, ETH Zurich, 8092 Zurich, Switzerland*
[2] *QuSoft, University of Amsterdam, the Netherlands*
[3] *EECS Department, University of California Berkeley, USA*
[4] *Department of Physics of Complex Systems, Weizmann Institute of Science, Israel*

In device-independent quantum key distribution (DIQKD), an adversary prepares a device consisting of two components, distributed to Alice and Bob, who use the device to generate a secure key. The security of existing DIQKD schemes holds under the assumption that the two components of the device cannot communicate with one another during the protocol execution. This is called the *no-communication assumption* in DIQKD. Here, we show how to replace this assumption, which can be hard to enforce in practice, by a standard *computational assumption* from post-quantum cryptography: we give a protocol that produces secure keys even when the components of an adversarial device can exchange arbitrary quantum communication, assuming the device is computationally bounded. Importantly, the computational assumption only needs to hold during the protocol execution—the keys generated at the end of the protocol are *information-theoretically secure* as in standard DIQKD protocols.

arXiv:2010.04175v3 [quant-ph] 29 Jul 2022

I. INTRODUCTION

The security of classical public-key cryptography is based on the assumption that an adversary cannot solve a specific computational problem, e.g. a lattice problem [1]. A message encrypted with classical public-key cryptography only remains secret as long as this computational assumption holds. If a faster algorithm or more powerful hardware allows the adversary to break the computational assumption in the future, all past communication is at risk. In contrast, quantum key distribution (QKD) protocols generate keys that are *information-theoretically secure*, i.e., secure even against an all-powerful adversary, and are not compromised by advances in algorithms or hardware. The security of QKD protocols is based on certain assumptions (which depend on the specific protocol being considered) that need to hold *during* the execution of the protocol—violating the assumptions afterwards does *not* compromise the security of the key. This is known as *everlasting security* [2].

Early QKD protocols, such as the BB84 protocol [3], relied on the assumption that the quantum device used to generate the key is implemented as intended. Any deviation from the implementation analysed in the security proof can potentially lead to a security breach [4–7]. Device-independent QKD (DIQKD) protocols [8, 9] address this problem: instead of making assumptions about the inner workings of the device, the device is being *tested* as part of the protocol, as explained below. This form of security is considered the "gold-standard" of quantum cryptography [10]. In particular, it allows for security statements that hold even when the manufacturer of the quantum device is incompetent or malicious.[1]

The standard setting for DIQKD is shown in Fig. 1a. Alice and Bob each hold a component of a device prepared by a potentially malicious party called Eve. Alice's and Bob's components of the device and the adversary Eve share some quantum state, and Alice's and Bob's components perform some quantum measurement on their respective part of the state. The shared quantum state and the measurements used by the components of the device are unknown to Alice and Bob. Hence, the device is said to be uncharacterised. Alice and Bob can only observe the classical *input-output correlations* of their device: they supply classical inputs to the device (e.g., by pressing keys on a keyboard connected to the device) and receive classical outputs (e.g., by reading information displayed on its screen).

The security proofs of DIQKD protocols rely on the fact that a *violation of a Bell inequality* [11, 12] can only be achieved by measuring an entangled quantum state. Hence, if Alice and Bob observe that the classical input-output correlations of the device violate a Bell inequality, they can conclude, under certain conditions, that the two components must have been entangled. This can then be used to certify the randomness, or entropy, of the output bits produced by measuring the entangled state. This certified entropy, in turn, acts as the basis for proving the security of the protocol [13–16].

For a security proof based on Bell inequalities to be valid, certain conditions must hold (or be assumed to hold). A potential violation of one of these conditions is called a *loophole*. An open loophole translates directly to a security breach in any DI cryptographic protocol [17]. A fundamental and experimentally challenging loophole is the so-called *communication loophole*—even a classical device can violate a Bell inequality when Alice's and Bob's components can communicate. Therefore, to conclude that the correlations produced by the device must have arisen from measuring an entangled state, we must assume that the two components of the device cannot communicate during one round of the protocol.

* tmetger@ethz.ch

[1] A malicious manufacturer is one that produces a devices with the intention of gaining information about the supposedly secret key generated by the device.