

arXiv:2101.12739v1 [quant-ph] 29 Jan 2021

Secure Software Leasing Without Assumptions

Anne Broadbent * Stacey Jeffery † Sébastien Lord *
Supartha Podder * Aarthi Sundaram ‡

Abstract

Quantum cryptography is known for enabling functionalities that are unattainable using classical information alone. Recently, *Secure Software Leasing (SSL)* has emerged as one of these areas of interest. Given a target circuit C from a circuit class, SSL produces an encoding of C that enables a recipient to evaluate C, and also enables the originator of the software to *verify* that the software has been *returned* — meaning that the recipient has relinquished the possibility of any further use of the software. Clearly, such a functionality is unachievable using classical information alone, since it is impossible to prevent a user from keeping a copy of the software. Recent results have shown the achievability of SSL using quantum information for a class of functions called *compute-and-compare* (these are a generalization of the well-known *point functions*). These prior works, however all make use of setup or computational assumptions. Here, we show that SSL is achievable for compute-and-compare circuits *without any assumptions*.

Our technique involves the study of *quantum copy-protection*, which is a notion related to SSL, but where the encoding procedure inherently *prevents* a would-be quantum software pirate from *splitting* a single copy of an encoding for C into two parts, each of which enables a user to evaluate C. We show that point functions can be copy-protected *without any assumptions*, for a novel security definition involving one honest and one malicious evaluator; this is achieved by showing that from any quantum message authentication code, we can derive such an *honest-malicious* copy-protection scheme. We then show that a generic honest-malicious copy-protection scheme implies SSL; by prior work, this yields SSL for compute-and-compare functions.

1 Introduction

One of the defining features of quantum information is the *no-cloning* principle, according to which it is not possible, in general, to take an arbitrary quantum state and produce two copies of it [Par70, WZ82, Die82]. This principle is credited for many of the feats of quantum information in cryptography, including quantum key distribution (QKD) [BB84] and quantum money [Wie83]. (For a survey on quantum cryptography, see [BS16]).

The quantum no-cloning principle tells us that, in a certain sense, quantum information behaves more like a *physical* object than a digital one: there are situations where quantum information can be distributed and used, but it cannot be duplicated. One such example is quantum money [Wie83], in which a quantum system is used to encode a very basic type of information — the ability to verify authenticity. However, we can envisage quantum encodings that achieve richer levels of

*University of Ottawa, Ottawa, Canada. {abroadbe,slord050,spodder}@uottawa.ca
†QuSoft and CWI, Amsterdam, Netherlands. jeffery@cwi.nl
‡Microsoft Quantum, Redmond, USA. aarthi.sundaram@microsoft.com