



2017–
2021

arXiv:2103.12448v2 [quant-ph] 24 Jun 2021

Quantum-access security of the Winternitz one-time signature scheme

Christian Majenz*[1], Chanelle Matadah Manfouo†[2], and Maris Ozols‡[3]

[1]*Centrum Wiskunde & Informatica and QuSoft, The Netherlands*
[2]*African Institute for Mathematical Science & Quantum Leap Africa, Rwanda*
[3]*Institute for Logic, Language, and Computation, Korteweg-de Vries Institute for Mathematics, and Institute for Theoretical Physics, University of Amsterdam and QuSoft, The Netherlands*

Abstract

Quantum-access security, where an attacker is granted superposition access to secret-keyed functionalities, is a fundamental security model and its study has inspired results in post-quantum security. We revisit, and fill a gap in, the quantum-access security analysis of the Lamport one-time signature scheme (OTS) in the quantum random oracle model (QROM) by Alagic et al. (Eurocrypt 2020). We then go on to generalize the technique to the Winternitz OTS. Along the way, we develop a tool for the analysis of hash chains in the QROM based on the superposition oracle technique by Zhandry (Crypto 2019) which might be of independent interest.

Contents

1 Overview **2**
1.1 Introduction . . . 2
1.2 Summary of results . . . 3
1.3 Technical overview . . . 4

2 Preliminaries **5**
2.1 Quantum computing . . . 5
2.2 Tools from linear algebra . . . 6
2.3 Hash-based one-time signature schemes . . . 7
2.3.1 The Lamport OTS . . . 8
2.3.2 The Winternitz OTS . . . 8
2.4 Blind unforgeability . . . 9

3 Hash chains in the QROM **10**
3.1 Quantum hash chain sampling . . . 10
3.1.1 Additional details for the Lamport and Winternitz OTS . . . 12
3.2 Indistinguishability . . . 12

4 One-time BU security of the Lamport OTS **14**
4.1 Q measurement for Lamport OTS . . . 15
4.2 Invariant projector . . . 15
4.3 Hash queries before Sign query . . . 16
4.4 Query to the signing oracle . . . 17
4.5 Hash queries after Sign query . . . 20

*christian.majenz@cwi.nl
†cmatadah@quantumleapafrica.org
‡marozols@gmail.com