

2020–
2024







2020–
2024

# Towards Practical and Error-Robust Quantum Position Verification

Rene Allerstorfer[*1], Harry Buhrman[¶1,2], Florian Speelman[‡2], and Philip Verduyn Lunel[§1]

[1] *QuSoft, CWI Amsterdam, Science Park 123, 1098 XG Amsterdam, The Netherlands*
[2] *QuSoft, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, The Netherlands*

Dated: August 11, 2022

arXiv:2106.12911v2 [quant-ph] 10 Aug 2022

**Abstract**

Loss of inputs can be detrimental to the security of quantum position verification (QPV) protocols, as it may allow attackers to not answer on all played rounds, but only on those they perform well on. In this work, we study *loss-tolerant* QPV protocols. We propose a new fully loss-tolerant protocol $\mathsf{QPV}_{\mathsf{SWAP}}$, based on the SWAP test, with several desirable properties. The task of the protocol, which could be implemented using only a single beam splitter and two detectors, is to estimate the overlap between two input states. By formulating possible attacks as a semi-definite program (SDP), we prove full loss tolerance against unentangled attackers restricted to local operations and classical communication, and show that the attack probability decays exponentially under parallel repetition of rounds. We show that the protocol remains secure even if unentangled attackers are allowed to quantum communicate, making our protocol the first fully loss-tolerant protocol with this property. A detailed analysis under experimental conditions is conducted, showing that $\mathsf{QPV}_{\mathsf{SWAP}}$ remains fairly robust against equipment errors. We identify a necessary condition for security with errors and simulate one instance of our protocol with currently realistic experimental parameters, gathering that an attack success probability of $\leq 10^{-6}$ can be achieved by collecting just a few hundred conclusive protocol rounds.

## 1 Introduction

Geographical position is an important contributor to trust—for example, a message which provably comes from a secure location in a government institution, has automatic credence to actually be sent by that government. Position-based cryptography is the study of using position as a cryptographic credential. The most basic task here is to certify someone's position, but this can be extended to messages that can only be read at a certain location, or to *authenticating* that a message came (unaltered) from a certain location.

[*]Email: rene.allerstorfer@cwi.nl
[¶]Email: harry.buhrman@cwi.nl
[‡]Email: f.speelman@uva.nl
[§]Email: philip.verduyn.lunel@cwi.nl