

2020–
2022





arXiv:2107.11806v2 [quant-ph] 18 Oct 2023

Tight Bounds for the Randomized and Quantum Communication Complexities of Equality with Small Error

Olivier Lalonde* Nikhil S. Mande† Ronald de Wolf‡

Abstract

We investigate the randomized and quantum communication complexities of the well-studied Equality function with small error probability ε, getting the optimal constant factors in the leading terms in various different models.

The following are our results in the *randomized* model:

- We give a general technique to convert public-coin protocols to private-coin protocols by incurring a small multiplicative error at a small additive cost. This is an improvement over Newman's theorem [Inf. Proc. Let.'91] in the dependence on the error parameter.
- As a consequence we obtain a $(\log(n/\varepsilon^2)+4)$-cost private-coin communication protocol that computes the n-bit Equality function, to error ε. This improves upon the $\log(n/\varepsilon^3)+O(1)$ upper bound implied by Newman's theorem, and matches the best known lower bound, which follows from Alon [Comb. Prob. Comput.'09], up to an additive $\log\log(1/\varepsilon)+O(1)$.

The following are our results in various *quantum* models:

- We exhibit a one-way protocol with $\log(n/\varepsilon)+4$ qubits of communication for the n-bit Equality function, to error ε, that uses only pure states. This bound was implicitly already shown by Nayak [PhD thesis'99].
- We give a near-matching lower bound: any ε-error one-way protocol for n-bit Equality that uses only pure states communicates at least $\log(n/\varepsilon)-\log\log(1/\varepsilon)-O(1)$ qubits.
- We exhibit a one-way protocol with $\log(\sqrt{n}/\varepsilon)+3$ qubits of communication that uses *mixed* states. This is tight up to additive $\log\log(1/\varepsilon)+O(1)$, which follows from Alon'09.
- We exhibit a one-way entanglement-assisted protocol achieving error probability ε with $\lceil\log(1/\varepsilon)\rceil+1$ classical bits of communication and $\lceil\log(\sqrt{n}/\varepsilon)\rceil+4$ shared EPR-pairs between Alice and Bob. This matches the communication cost of the classical public coin protocol achieving the same error probability while improving upon the amount of prior entanglement that is needed for this protocol, which is $\lceil\log(n/\varepsilon)\rceil+O(1)$ shared EPR-pairs.

Our upper bounds also yield upper bounds on the approximate rank, approximate nonnegative-rank, and approximate psd-rank of the Identity matrix. As a consequence we also obtain improved upper bounds on these measures for a function that was recently used to refute the randomized and quantum versions of the log-rank conjecture (Chattopadhyay, Mande and Sherif [J. ACM'20], Sinha and de Wolf [FOCS'19], Anshu, Boddu and Touchette [FOCS'19]).

*DIRO, Université de Montréal. Supported by the Natural Sciences and Engineering Research Council of Canada (NSERC). olivier.lalonde.1@umontreal.ca

†University of Liverpool, UK. Work done while the author was a postdoc at CWI, Amsterdam, and supported by the Dutch Research Council (NWO) through QuantERA ERA-NET Cofund project QuantAlgo (project number 680-91-034). mande@liverpool.ac.uk

‡QuSoft, CWI and University of Amsterdam, the Netherlands. Partially supported by the Dutch Research Council (NWO/OCW), as part of the Quantum Software Consortium programme (project number 024.003.037), and through QuantERA ERA-NET Cofund project QuantAlgo (680-91-034). rdewolf@cwi.nl