

2020–
2024







2020–
2024



arXiv:2208.04341v1 [quant-ph] 8 Aug 2022

On the Role of Quantum Communication and Loss in Attacks on Quantum Position Verification

Rene Allerstorfer*[1], Harry Buhrman¶[1,2], Florian Speelman‡[2], and Philip Verduyn Lunel§[1]

[1] *QuSoft, CWI Amsterdam, Science Park 123, 1098 XG Amsterdam, The Netherlands*
[2] *QuSoft, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, The Netherlands*

Dated: August 10, 2022

Abstract

We study the role of quantum communication in attacks on quantum position verification. In this work, we construct the first known example of a QPV protocol that is provably secure against unentangled attackers restricted to classical communication, but can be perfectly attacked by local operations and a single round of simultaneous quantum communication indicating that allowing for quantum communication may break security. We also show that any protocol secure against classical communication can be transformed into a protocol secure against quantum communication. We further show, using arguments based on the monogamy of entanglement, that the task of Bell state discrimination cannot be done locally with a single round of quantum communication, not even probabilistically (when we allow attackers to say loss sometimes), making this the first fully loss-tolerant QPV task secure against quantum communication attacks. Finally, we observe that any multi-round QPV protocol can be attacked with a linear amount of entanglement if the loss is high enough.

1 Introduction

Geographical position is an important contributor to trust—for example, a message which provably comes from a secure location in a government institution, has automatic credence to actually be sent by that government. Position-based cryptography is the study of using position as a cryptographic credential. The most basic task here is to certify someone's position, but this can be extended to messages that can only be read at a certain location, or to *authenticating* that a message came (unaltered) from a certain location.

We will focus on the task of *position verification*, which can be used as the building block for tasks like position-based authentication. For simplicity, the focus will be on the one-dimensional case, i.e. verifying one's position on a line, but the relevant ideas generalize readily to more dimensions. In

*Email: rene.allerstorfer@cwi.nl
¶Email: harry.buhrman@cwi.nl
‡Email: f.speelman@uva.nl
§Email: philip.verduyn.lunel@cwi.nl