


2016–
2022



2019–
2023

Basic quantum subroutines: finding multiple marked elements and summing numbers

Joran van Apeldoorn[1], Sander Gribling[2], and Harold Nieuwboer[3]

[1]IViR and QuSoft, University of Amsterdam, The Netherlands
[2]Department of Econometrics and Operations Research, Tilburg University, Tilburg, The Netherlands
[3]Korteweg–de Vries Institute for Mathematics and QuSoft, University of Amsterdam, The Netherlands and Faculty of Computer Science, Ruhr University Bochum, Germany and Department of Mathematical Sciences, University of Copenhagen, Denmark

arXiv:2302.10244v3 [quant-ph] 5 Mar 2024

We show how to find all k marked elements in a list of size N using the optimal number $O(\sqrt{Nk})$ of quantum queries and only a polylogarithmic overhead in the gate complexity, in the setting where one has a small quantum memory. Previous algorithms either incurred a factor k overhead in the gate complexity, or had an extra factor $\log(k)$ in the query complexity.

We then consider the problem of finding a multiplicative δ-approximation of $s = \sum_{i=1}^{N} v_i$ where $v = (v_i) \in [0,1]^N$, given quantum query access to a binary description of v. We give an algorithm that does so, with probability at least $1-\rho$, using $O(\sqrt{N}\log(1/\rho)/\delta)$ quantum queries (under mild assumptions on ρ). This quadratically improves the dependence on $1/\delta$ and $\log(1/\rho)$ compared to a straightforward application of amplitude estimation. To obtain the improved $\log(1/\rho)$ dependence we use the first result.

1 Introduction

1.1 Finding multiple marked elements in a list

Grover's famous search algorithm [Gro96] can be used to find a marked element in a list quadratically faster than possible classically. Formally it can be used to solve the following problem: given a bit string $x \in \{0,1\}^N$, $x \neq 0$, find an index $i \in [N]$ such that $x_i = 1$.

In this work we consider the problem of finding *all* indices $i \in [N]$ for which $x_i = 1$. We give a query-optimal quantum algorithm with polylogarithmic gate overhead in the setting where one has a *small quantum memory*. We explain below why this last assumption makes the problem non-trivial. This improves over the previous state-of-the-art: previous algorithms were either query-optimal but with a polynomial gate overhead, or had a polylogarithmic gate overhead but also a logarithmic overhead in the query count.

A well-known query-optimal algorithm for the problem is as follows [dGdW02, Lem. 2]. Let k be the Hamming weight $|x| := \sum_{i=1}^{N} x_i$ of x. For ease of exposition, suppose the algorithm knows k. (For our results we will work with weaker assumptions such as knowing only an upper bound on k, or an estimate of it, see Section 3. We also ignore failure probabilities in this part of

Joran van Apeldoorn: work@bitofbytes.com
Sander Gribling: s.j.gribling@tilburguniversity.edu
Harold Nieuwboer: hani@math.ku.dk