

2021–
2025

Quantum Pseudorandomness Cannot Be Shrunk In a Black-Box Way

Samuel Bouaziz--Ermann[1] and Garazi Muguruza[2,3]

[1] Sorbonne Université, CNRS, LIP6, France
[2] Informatics Institute, University of Amsterdam, Netherlands
[3] QuSoft, Netherlands

arXiv:2402.13324v1 [quant-ph] 20 Feb 2024

Abstract. Pseudorandom Quantum States (PRS) were introduced by Ji, Liu and Song as quantum analogous to Pseudorandom Generators. They are an ensemble of states efficiently computable but computationally indistinguishable from Haar random states. Subsequent works have shown that some cryptographic primitives can be constructed from PRSs. Moreover, recent classical and quantum oracle separations of PRS from One-Way Functions strengthen the interest in a purely quantum alternative building block for quantum cryptography, potentially weaker than OWFs.
However, our lack of knowledge of extending or shrinking the number of qubits of the PRS output still makes it difficult to reproduce some of the classical proof techniques and results. Short-PRSs, that is PRSs with logarithmic size output, have been introduced in the literature along with cryptographic applications, but we still do not know how they relate to PRSs. Here we answer half of the question, by showing that it is not possible to shrink the output of a PRS from polynomial to logarithmic qubit length while still preserving the pseudorandomness property, in a relativized way. More precisely, we show that relative to Kretschmer's quantum oracle (TQC 2021) short-PRSs cannot exist (while PRSs exist, as shown by Kretschmer's work).

1 Introduction

Pseudorandomness is an important concept in cryptography since almost all relevant classical cryptographic primitives require the existence of one-way functions (OWF) or equivalent objects such as pseudorandom generators (PRG) and pseudorandom functions (PRF) [HILL99]. It corresponds to a deterministic function whose output cannot be distinguished from the uniform distribution by a computationally bounded algorithm.

In 2018, Ji, Liu and Song [JLS18] introduced a quantum analog of PRGs, called *Pseudorandom Quantum States* (PRS) that consists of a family of polynomial size keyed-states $\{|\phi_k\rangle\}_{k\in\mathcal{K}}$ such that no quantum polynomial-time algorithm can distinguish between a polynomial number of copies[4] of a randomly sampled element from the PRSs family or a polynomial number of copies of a Haar-random state (see Definition 1 for a formal definition). We already know how to construct several cryptographic primitives from (variants of) PRSs: public key encryption with quantum keys [BGHD+23], quantum digital signatures [MY22b], pseudo one-time pad encryption schemes [AQY22], statistically binding and computationally hiding commitments [AQY22,MY22a,KT23] and quantum computational zero knowledge proofs [BCQ23]. Such rapid interest derives probably from the fact that PRSs can be constructed from OWFs [JLS18] (and thus PRGs), but there are oracle separations found between OWFs and PRSs [Kre21,KQST23], which makes them a potentially weaker building block for quantum cryptography, with a purely quantum description.

Classically, practical applications of PRGs require stretching the output, which can be done arbitrarily by just using the output of the PRG as an input and roughly composing the PRG with itself. However, no analogous intuitive construction is possible with PRSs because the input is a classical bit string and the output is a quantum state. Moreover, although classically shrinking a PRG does not make sense, it is still possible by discarding part of the output of the original PRG. Quantumly, discarding half of a quantum

[4] The reason we give the adversary a polynomial number of copies of the state is that an arbitrary quantum state cannot be cloned, by the no-cloning theorem.