

2022–
2025

Efficient learning of quantum states prepared with few fermionic non-Gaussian gates

Antonio Anna Mele[1,*] and Yaroslav Herasymenko[2,3,4,†]

[1]*Dahlem Center for Complex Quantum Systems, Freie Universität Berlin, 14195 Berlin, Germany*
[2]*QuSoft and CWI, Science Park 123, 1098 XG Amsterdam, The Netherlands*
[3]*QuTech, TU Delft, P.O. Box 5046, 2600 GA Delft, The Netherlands*
[4]*Delft Institute of Applied Mathematics, TU Delft, 2628 CD Delft, The Netherlands*

(Dated: January 30, 2025)

The experimental realization of increasingly complex quantum states underscores the pressing need for new methods of state learning and verification. In one such framework, quantum state tomography, the aim is to learn the full quantum state from data obtained by measurements. Without prior assumptions on the state, this task is prohibitively hard. Here, we present an efficient algorithm for learning states on n fermion modes prepared by any number of Gaussian and at most t non-Gaussian gates. By Jordan-Wigner mapping, this also includes n-qubit states prepared by nearest-neighbour matchgate circuits with at most t SWAP-gates. Our algorithm is based exclusively on single-copy measurements and produces a classical representation of a state, guaranteed to be close in trace distance to the target state. The sample and time complexity of our algorithm is $\mathrm{poly}(n, 2^t)$; thus if $t = \mathcal{O}(\log(n))$, it is efficient. We also show that, if t scales *slightly* more than logarithmically, any learning algorithm to solve the same task must be inefficient, under common cryptographic assumptions. We also provide an efficient property testing algorithm that, given access to copies of a state, determines whether such a state is far or close to the set of states for which our learning algorithm works. In addition to the outputs of quantum circuits, our tomography algorithm is efficient for some physical target states, such as those arising in time dynamics and low-energy physics of impurity models. Beyond tomography, our work sheds light on the structure of states prepared with few non-Gaussian gates and offers an improved upper bound on their circuit complexity, enabling an efficient circuit compilation method.

arXiv:2402.18665v3 [quant-ph] 29 Jan 2025

Introduction

Quantum state tomography is the task of reconstructing a classical description of a quantum state from experimental data [1, 2]. Beyond its foundational significance in quantum information theory, it stands as the gold standard for verification and benchmarking of quantum devices [2]. However, in the absence of any prior assumptions on the state to be learned, one encounters necessarily the *curse of dimensionality* of the Hilbert space: learning the classical description of a generic quantum state demands resources that grow exponentially with the number of qubits [1, 3]. Simply storing and outputting the density matrix of a state already results in an exponential cost in time. This raises the crucial question of identifying interesting classes of quantum states that can be efficiently learned using a number of state copies and time scaling at most *polynomially* with the system size. Only a few classes of states are currently known to be efficiently learnable — in particular, matrix product states [2, 4], finitely-correlated states [5], high-temperature Gibbs states [6], states prepared by shallow quantum circuits [7–9], stabilizer states [10], quantum phase states [11], and fermionic Gaussian states [12, 13]. The latter class of states comprises those prepared by fermionic Gaussian circuits [14], also referred to as free fermionic (non-interacting) evolutions or fermionic linear-optics circuits [15, 16]. Via Jordan-Wigner mapping, such states on n fermionic modes can also be viewed as n-qubit states, prepared by generalized matchgate circuits [16–18]. Fermionic Gaussian states states play a key role in condensed matter physics and quantum chemistry, via the Hartree-Fock method and in the context of Fermi Liquid and Bardeen-Cooper-Schrieffer theories [19–22]. These states are also essential in understanding many exactly solvable spin models [23–25]. In quantum computing, fermionic Gaussian states are primarily recognized for their efficient classical simulability [15, 17, 18]. As in the case of Clifford circuits, for which the introduction of magic gates, such as T-gates, allows to reach universal quantum computation [26], also for the case of Gaussian circuits the inclusion of certain magic gates [27–29], for example SWAP gates [28], allows to reach universality. If the number t of T-gates in a Clifford circuit is low, the resulting states can still be efficiently simulated classically [30–32]; it has also been recently demonstrated that such states, termed as t-doped stabilizer states [33, 34], are still efficiently learnable [35–37]. Similarly, in the past year, it has been shown that Gaussian circuits with a few magic gates are also classically simulable [38–40]. However, the learnability of such "t-doped fermionic Gaussian states" remains unknown and this motivates the core-question of our work:

Can we efficiently learn states prepared by Gaussian operations (e.g. matchgates) and a few magic gates?

We answer it by proposing a quantum algorithm of polynomial time and sample complexity that uses only single-copy measurements and learns a succint classical description of a t-doped fermionic Gaussian state; the learned state is guaranteed to be close to the true state in trace distance. Our presentation is framed in the language of qubits, but the results seamlessly translate into the fermionic formalism. Our learning algorithm may also be feasible to implement in near-term fermionic analog quantum