

2020–
2024



2021–
2025



Continuous-variable Quantum Position Verification secure against entangled attackers

Rene Allerstorfer[1], Llorenç Escolà-Farràs[2], Arpan Akash Ray[3], Boris Škorić[3], and Florian Speelman[2]

[1] *QuSoft & CWI Amsterdam, The Netherlands*
[2] *QuSoft & Informatics Institute, University of Amsterdam, The Netherlands*
[3] *TU Eindhoven, The Netherlands*

April 23, 2024

arXiv:2404.14261v1 [quant-ph] 22 Apr 2024

Abstract

Motivated by the fact that coherent states may offer practical advantages it was recently shown that a continuous-variable (CV) quantum position verification (QPV) protocol using coherent states could be securely implemented if and only if attackers do not pre-share any entanglement. In the discrete-variable (DV) analogue of that protocol it was shown that modifying how the classical input information is sent from the verifiers to the prover leads to a favourable scaling in the resource requirements for a quantum attack. In this work, we show that similar conclusions can be drawn for CV-QPV. By adding extra classical information of size n to a CV-QPV protocol, we show that the protocol, which uses a coherent state and classical information, remains secure, even if the quantum information travels arbitrarily slow, against attackers who pre-share CV (entangled) states with a linear (in n) cutoff at the photon number. We show that the protocol remains secure for certain attenuation and excess noise.

Contents

1 Introduction 1

2 Preliminaries 3

3 The $\mathrm{QPV}^{f}_{\mathrm{coh}}$ protocol 4

4 Security against bounded entanglement 6
4.1 Bounding attack success probability after repeated i.i.d. rounds 11

5 Concrete linear bounds for given experimental parameters 12
5.1 Perfect channel 12
5.2 Imperfect channel 13

6 Open problems 13

1 Introduction

Position-based cryptography utilises the geographic location of a party as the only cryptographic credential to authenticate it, without further assumptions. For instance, to authenticate a website or online media one could verify that the server is located *where* it should be or that the media was recorded *where* it claims to have been (instead of being created by a powerful AI or untrusted parties, for example). Part of position-based cryptography is the task of position verification, where an untrusted prover aims to convince verifiers that he is present at a certain position P.