

2022–
2025

Solving Free Fermion Problems on a Quantum Computer

Maarten Stroeks,[1,2,*] Daan Lenterman,[3] Barbara M. Terhal,[1,2] and Yaroslav Herasymenko[2,4,†]

[1] *QuTech, TU Delft, Lorentzweg 1, 2628 CJ Delft, The Netherlands*
[2] *Delft Institute of Applied Mathematics, TU Delft, 2628 CD Delft, The Netherlands*
[3] *Department of Physics, ETH Zürich, CH-8093 Zürich, Switzerland*
[4] *QuSoft and CWI, Science Park 123, 1098 XG Amsterdam, The Netherlands*

Simulating noninteracting fermion systems is a common task in computational many-body physics. In absence of translational symmetries, modeling free fermions on N modes usually requires poly(N) computational resources. While often moderate, these costs can be prohibitive in practice when large systems are considered. We present several free-fermion problems that can be solved by a quantum algorithm with substantially reduced computational costs. The memory costs are exponentially improved, poly log(N). The runtime improvement, compared to the best known classical algorithms, is either exponential or significantly polynomial, depending on the geometry of the problem. The simulation of free-fermion dynamics belongs to the BQP-hard complexity class. This implies (under standard assumptions) that our algorithm yields an exponential speedup for *any* classical algorithm at least for some geometries. The key technique in our algorithm is the block-encoding of objects such as correlation matrices and Green's functions into a unitary. We demonstrate how such unitaries can be efficiently realized as quantum circuits, in the context of dynamics and thermal states of tight-binding Hamiltonians. The special cases of disordered and inhomogeneous lattices, as well as large non-lattice graphs, are presented in detail. Finally, we show that our simulation algorithm generalizes to other promising targets, including free boson systems.

arXiv:2409.04550v4 [quant-ph] 26 Sep 2025

I. INTRODUCTION AND BACKGROUND

Quantum many-body dynamics can be naturally simulated by a quantum computer [1], enabling its applications in condensed matter and quantum chemistry. For a system of size N, standard quantum algorithms use poly(N) resources for such simulations. It implies an exponential advantage over classical methods, when dealing with a generic many-body system. Such a general advantage may not hold in special cases of interest, such as the modeling of free fermions, where the best classical algorithms also have poly(N) cost [2–4]. This classical efficiency has been key to many successes of computational physics, as free fermions model a variety of systems in condensed matter and quantum chemistry; they have also been used in computational strategies for solving interacting fermion systems, using mean-field (Hartree-Fock), perturbative methods or dynamical mean-field theory. Nonetheless, in the practical simulations of noninteracting fermions, even the most efficient numerical methods become too expensive for large systems. This motivates the key question of this work: can a quantum computer boost free-fermion simulations beyond what can be done classically? We answer this question in the affirmative, presenting quantum algorithms with an exponential speedup and memory compression for several free-fermion problems.

To appreciate the value of such an exponential reduction, consider numerical simulations of free-fermion models of materials and interfaces for quantum transport [5, 6]. These can become prohibitive when involving more than $N = 10^9$ modes, which is of practical interest when simulating 3-dimensional lattice models. Upon compression, a system of 10^9 sites can be described by $n = 30$ qubits. Larger systems of practical interest could still be accessed with moderately sized quantum computers. Indeed, even simulating one mole ($N \simeq 10^{24}$) of fermionic modes requires fewer than $n = 80$ qubits in compressed form. This opens the door to modeling free fermions near the thermodynamic limit — a desired but often challenging goal.

Our result is based on an understanding of the reduced classical complexity of free-fermion systems. As an inspiration, we used the fact that the matchgate computations and the dynamics of free fermion problems on $N = 2^n$ modes can be simulated in compressed form, using $O(n)$ *space* on a quantum computer [7–11]. In this work, we go beyond these memory compression results to identify free fermion problems that also permit an exponentially improved, poly(n) quantum *run-time*. Our key idea is to represent the relevant 2^n-sized object—such as the correlation matrix or a Green's function of a free-fermion state—as a block of an n-qubit unitary. This unitary can be given as an efficient quantum circuit; we provide explicit construction methods by leveraging the modern quantum algorithm toolbox of block-encoding manipulations [12–16]. In particular, we show how to construct the desired unitary for free-fermion states arising from time dynamics or thermal equilibrium. Given block-encodings of the aforementioned objects into a circuit, we show how to accurately extract various physical quantities for a state, including the occupation number on a given site, or energy density across the entire system. We analyze the application of our methods to free-fermion models on d-dimensional lattices and expander graphs. For the particular case of d-dimensional lattices,

* m.e.h.m.stroeks@tudelft.nl
† yaroslav@cwi.nl