

# Getting almost all the bits from a quantum random access code

Han-Hsuan Lin* Ronald de Wolf†

June 11, 2025

arXiv:2506.01903v1 [quant-ph] 2 Jun 2025

**Abstract**

A quantum random access code (QRAC) is a map $x \mapsto \rho_x$ that encodes $n$-bit strings $x$ into $m$-qubit quantum states $\rho_x$, in a way that allows us to recover any one bit of $x$ with success probability $\geq p$. The measurement on $\rho_x$ that is used to recover, say, $x_1$ may destroy all the information about the other bits; this is in fact what happens in the well-known QRAC that encodes $n = 2$ bits into $m = 1$ qubits. Does this generalize to large $n$, i.e., could there exist QRACs that are so "obfuscated" that one cannot get much more than one bit out of them? Here we show that this is not the case: for every QRAC there exists a measurement that (with high probability) recovers the full $n$-bit string $x$ up to small Hamming distance, even for the worst-case $x$.

## 1 Introduction

### 1.1 Quantum Random Access Codes

Quantum states of $m$ qubits are described by $2^m$ complex amplitudes, and it is tempting to try to use this exponential "space" to encode a lot of classical information in a quantum state. Holevo's theorem [Hol73] says that in general we cannot use this exponential space: if we encode some classical random variable $X$ in an $m$-qubit quantum state $\rho_X$ (via a map $x \mapsto \rho_x$), and then do a measurement on $\rho_X$ to produce a classical random variable $Y$, then the mutual information between $X$ and $Y$ is at most $m$. So we cannot cram more than $m$ bits of information into $m$ qubits.

*Quantum random access* codes, first introduced in [ANTV99], address a more subtle situation where we demand less from the decoding: here $x \in \{0,1\}^n$ and we only want to be able to recover the bit $x_i$ of $x$ from $\rho_x$ with success probability $p > 1/2$, for any $i \in [n]$ of our choice. Note that this is different from recovering *all* bits of $x$, since the measurement that recovers $x_1$ can change the $m$-qubit state, making it harder (or even impossible) to recover other bits of $x$. More formally:

**Definition 1** *An $(n, m, p)$-quantum random access code (QRAC) is a map $x \mapsto \rho_x$ from the set of $n$-bit strings to the set of $m$-qubit mixed states, such that for each $i \in [n]$ there exists a 2-outcome POVM $\{M_0, M_1\}$ such that for each $x \in \{0,1\}^n$ and $b \in \{0,1\}$ we have $\mathrm{Tr}(M_b \rho_x) \geq p$ if $x_i = b$.*

*Department of Computer Science, National Tsing Hua University, Hsinchu 30013, Taiwan. Supported by NSTC QC project under Grant no. 111-2119-M-001-006-. linhh@cs.nthu.edu.tw

†QuSoft, CWI and University of Amsterdam, the Netherlands. Partially supported by the Dutch Research Council (NWO) through Gravitation-grant Quantum Software Consortium, 024.003.037. rdewolf@cwi.nl