

Experimental Efficient Influence Sampling of Quantum Processes

Hao Zhan,[1,*] Zongbo Bao,[2,3,*] Zekun Ye,[2] Qianyi Wang,[1] Minghao Mi,[1] Penghui Yao,[2,4,†] and Lijian Zhang[1,‡]

[1] *National Laboratory of Solid State Microstructures, Key Laboratory of Intelligent Optical Sensing and Manipulation, College of Engineering and Applied Sciences, Jiangsu Physical Science Research Center, and Collaborative Innovation Center of Advanced Microstructures, Nanjing University, Nanjing, 210093, China*

[2] *State Key Laboratory for Novel Software Technology, New Cornerstone Science Laboratory, Nanjing University, Nanjing 210093, China*

[3] *QuSoft and CWI, Amsterdam, 1098 XG, The Netherlands*

[4] *Hefei National Laboratory, Hefei 230088, China.*

(Dated: June 12, 2025)

Characterizing quantum processes paves the way for unlocking the full potential of quantum systems. However, quantum process tomography demands intensive resources and becomes infeasible on large-scale quantum devices. Other methods have explored advanced strategies, yet challenges in experimental feasibility and scalability persist. To address this issues, we introduce influence sampling that efficiently extracts the key *influence* of a quantum process on qubit subsets using at most three distinct single-qubit test gates. Using a photonic platform, we experimentally demonstrate influence sampling and apply it to testing and learning quantum junta processes, determining whether a process acts non-trivially on only a subset of qubits and subsequently learning that process. In addition, we confirm the scalability of influence sampling by deploying it in larger systems. These results establish influence sampling as a powerful and scalable process characterization technique, facilitating efficient device assessment and noisy qubit identification.

arXiv:2506.07103v1 [quant-ph] 8 Jun 2025

I. INTRODUCTION

The development of large-scale, multi-qubit quantum computers aims to achieve promising quantum advantages in practical applications, markedly outperforming classical systems [1–4]. Realizing this potential requires accurate learning and characterizing the building blocks of quantum computers, such as quantum gates and processes, for performance assessment and noise diagnosis across various architectures [5–8]. Fully characterizing an n-qubit process through quantum process tomography (QPT) [9–12] demands $O(4^n)$ queries, rendering it impractical for large systems due to exponential resource consumption [13]. Efforts have been devoted to developing novel techniques that overcome the limitations of QPT, such as randomized benchmarking [14], classical shadow [15, 16], and quantum verification [17, 18]. Yet, these approaches often rely on multi-qubit gates or extensive prior knowledge [19], limiting their practical implementation and scalability. This motivates the exploration of efficient and hardware-friendly methods that extract partial, yet particularly relevant, information about the quantum process.

A key property, often overlooked yet crucial in practice, is how strongly a quantum process influences specific qubits. For instance, an n-qubit quantum processor might have several faulty qubits where noise corrupts identity operations, leading to irreducibly high influence on them. In contrast, some processors may effectively utilize only k tunable qubits, leaving the others unaffected with near-zero influence. Identifying which qubits are most and least influenced by the quantum process is therefore essential. To this end, we introduce *influence sampling*, a method that quantifies the influence function $\mathrm{Inf}_S[\Phi]$ of a quantum process Φ on any subset S of qubits, generalizing the concept of influence from classical Boolean functions [20–22].

Influence sampling is particularly valuable when a quantum process significantly affects only a small subset of qubits. This scenario naturally leads to the concept of a quantum k-junta [22–24], generalizing Boolean juntas [20], where an n-qubit quantum process Φ acts non-trivially only on a subset S of at most k qubits ($k < n$). Such a process can be modeled as $\Phi = \Phi_S \otimes \mathcal{I}_{S^c}$, where Φ_S acts on the influential qubits S, and $\mathcal{I}_{S^c}$ is the identity process on the remaining qubits. Testing Boolean juntas classically has been extensively explored in computer science [25–29]. While quantum algorithms exist for testing Boolean juntas [30, 31] and unitary quantum juntas [32], these often rely on entangled operations in state preparation and measurement. Recent work [22] introduced an efficient influence sampling algorithm requiring only single-qubit test gates and leveraged it to develop quantum junta process testing (QJPT) and quantum junta process learning (QJPL) algorithms with significantly reduced query complexity. The QJPT algorithm can determine if a quantum process is a k-junta with a linear query complexity of $O(k)$, and the QJPL algorithm reduces the query complexity from $O(4^n)$ to $O(4^k)$ compared to QPT. However, the proposed algorithms assume ideal state preparation, gates and measurement, limiting their direct applicability to real-world scenarios with inherent noise and imperfections.

* These authors contributed equally to this work.
† pyao@nju.edu.cn
‡ lijian.zhang@nju.edu.cn