

Quasi-continuous sub-μK strontium source without a high-finesse cavity stabilized laser

Sana Boughdachi [1, 2, *] Benedikt Heizenreder [1, *] Ananya Sitaram [1] Erik Dierikx [3] Yan Xie [3] Sander Klemann [4] Paul Klop [4] Jeroen Koelemeij [5] Rafał Wilk [2] Florian Schreck [1, 6] and Andreas Brodschelm [2, †]

[1] *Van der Waals-Zeeman Institute, Institute of Physics, University of Amsterdam, Science Park 904, 1098 XH Amsterdam, The Netherlands*
[2] *Toptica Photonics SE, Lochhamer Schlag 19, 82166 Gräfelfing, Germany*
[3] *VSL National Metrology Institute, Thijsweg 11, 2629 JA Delft, the Netherlands*
[4] *SURF, Moreelsepark 48, 3511 EP Utrecht, The Netherlands*
[5] *LaserLaB, Department of Physics and Astronomy, Vrije Universiteit Amsterdam, De Boelelaan 1081, 1081 HV Amsterdam, the Netherlands*
[6] *QuSoft, Science Park 123, 1098 XG Amsterdam, The Netherlands*

(Dated: August 1, 2025)

We demonstrate a quasi-continuous sub-μK strontium source achieved without the use of a high-finesse cavity-locked laser. Our frequency reference is based on a dispersion-optimized, fiber-based frequency comb that enables sub-kHz linewidths. The long-term stability of the comb is defined by an external RF reference: either a 10 MHz RF signal from the Dutch Metrology Institute (VSL), or a tunable RF source whose long-term stability is maintained by monitoring and stabilizing the position of a narrow-line magneto-optical trap (MOT) [1, 2]. The comb-stabilized system is benchmarked against a conventional cavity-locked laser and achieves comparable performance in broadband and single-frequency MOTs using the narrow $^1S_0 \rightarrow {}^3P_1$ laser cooling transition. We generate high-flux, sub-μK samples of all three bosonic strontium isotopes and demonstrate quasi-continuous outcoupling from the MOT. These results highlight the system's suitability for compact, robust, and field-deployable continuous cold atom devices.

arXiv:2507.23617v1 [physics.atom-ph] 31 Jul 2025

I. INTRODUCTION

The development of ultra-cold atomic sources has revolutionized precision measurement, driving progress in optical lattice clocks [3–5] and other quantum sensors [6–8]. In recent years, there has been growing interest in continuous high-density ultra-cold atomic sources [9–17]. Strontium, as an alkaline-earth element, is particularly well-suited for continuous cold atom sources due to its narrow optical transitions, which enable narrow-linewidth laser cooling schemes [18–22]. Traditionally, such narrow-line cooling schemes rely on laser systems stabilized to high-finesse optical cavities [23, 24], which can provide laser linewidths well below that of the narrow cooling transition. While these cavities offer excellent short-term frequency stability, they require meticulous alignment and are sensitive to environmental perturbations that limit operational robustness and long-term reliability. Thus, a key challenge is to achieve narrow-linewidth laser stabilization without reliance on environmentally sensitive cavities. One alternative stabilization method is via a frequency comb, though typical fiber-based combs suffer from linewidth broadening due to oscillator pump-induced noise, environmental fluctuations, and quantum noise, compromising their use in narrow-linewidth laser cooling or other precision applications [25].

To overcome these limitations, we introduce a dispersion-engineered frequency comb and demonstrate its use for a quasi-continuous ultracold strontium source. The frequency comb is generated using mode-locked Er:fiber oscillators, which are intrinsically insensitive to pump-induced fluctuations by dispersion engineering. These measures preserve the coherence and spectral purity of individual comb teeth, enabling direct laser stabilization with sub-kHz precision by locking its repetition-rate to an RF reference. The reduced susceptibility to thermal and vibrational noise also enables easier integration into compact, transportable quantum platforms. Through a non-linear conversion processes, a broad spectral range extending from 420 nm to beyond 2000 nm can be obtained, creating an architecture adaptable for narrow-linewidth laser cooling of strontium at 429 THz but also for a wide range of other narrow-linewidth alkaline-earth(-like) [26, 27] and lanthanide atoms [28, 29]. We use our fully fiber-based frequency comb to generate the ultracold strontium source by directly locking the narrow-line cooling laser to it without any need of a high-finesse free-space reference cavity. Thanks to its broad coverage and flexible offset-locking capabilities, our system supports laser cooling of all three stable bosonic strontium isotopes using a single unified laser architecture. Combined with a robust laser cooling setup, this enables the generation of a continuous source of ultra-cold strontium atoms at μK temperatures. To ensure long-term frequency stability of the comb, its repetition rate must be stabilized to an external reference. We employ two approaches, which we compare against a cavity-based laser system: a highly stable external RF

* These authors contributed equally to this work.
† NarrowLineComb@strontiumBEC.com