

Exponential Advantage of Multipartite Entanglement over Quantum Communication with Applications to Bounded-Storage Cryptography

Ananya Chakraborty,[1,*] Manik Banik,[1] and Ronald de Wolf[2]

[1]*S. N. Bose National Centre for Basic Sciences, Block JD, Sector III, Salt Lake, Kolkata 700 106, India.*
[2]*QuSoft, CWI and University of Amsterdam, the Netherlands.*

We establish an exponential communication advantage enabled by multipartite quantum entanglement. Building on the bipartite Hidden Matching problem, we introduce a communication task involving multiple spatially separated senders and a single receiver. We show that a shared Greenberger–Horne–Zeilinger state enables completion of this task using only logarithmically many bits of classical communication from each sender. In contrast, without preshared entanglement, any protocol achieving high success probability requires polynomial communication from at least one sender, even when *quantum* communication is allowed. Thus, classical communication assisted by multipartite entanglement can be exponentially more powerful than quantum communication without preshared entanglement. As a cryptographic application, we construct a seeded two-source randomness extractor and establish an exponential separation between entangled and unentangled quantum side-information. Specifically, compromising the extractor with two unentangled quantum states storing information about the two sources, respectively, requires polynomial-size memory, whereas exponentially smaller quantum memory suffices in the presence of a small amount of shared entanglement.

arXiv:2607.27957v1 [quant-ph] 30 Jul 2026

I. INTRODUCTION

Quantum entanglement, '*the characteristic trait of quantum mechanics*' [1], underlies some of the most profound phenomena in physics, including the Einstein-Podolsky-Rosen paradox, Schrödinger steering, and Bell nonlocality [2–6]. Beyond its foundational significance, entanglement is a key resource for quantum information processing, enabling communication, computation, and cryptographic tasks that are impossible or substantially less efficient within classical frameworks [7–15]. The communication advantages afforded by bipartite entanglement are now reasonably well understood [16]. By contrast, *multipartite* entanglement possesses a far richer structure, including genuinely multipartite forms that cannot be reduced to collections of bipartite correlations [17–19]. Despite remarkable experimental advances in generating and controlling multipartite entangled states [20–24], our understanding of how such states enhance distributed information-processing tasks remains comparatively limited. Communication complexity provides a natural framework for investigating this question. In communication complexity tasks, spatially separated parties seek to evaluate a global property of distributed inputs while exchanging as little communication as possible [25, 26]. Quantum resources can dramatically reduce communication costs and, in several notable instances, yield exponential advantages over classical protocols [27–30]. However, most known exponential separations are in bipartite settings [31–36], leaving open the question whether multipartite entanglement alone can provide comparable advantages in communication tasks.

Here, we address this question by introducing a multipartite one-way communication task wherein multiple spatially separated senders receive classical inputs and a single receiver must produce an output satisfying a prescribed global relation. We show that a Greenberger-Horne-Zeilinger (GHZ) state [37–39] shared among all the parties enables success using only $O(\log n)$ bits of *classical* communication from each sender. The protocol exploits the multipartite phase correlations of the GHZ state to encode the local inputs and recover the required global relation at the receiver. In contrast, any protocol achieving a high success probability without preshared entanglement requires polynomial communication from at least one sender. Remarkably, this lower bound continues to hold even when unrestricted *quantum* communication from the senders to the receiver is permitted. Consequently, classical communication assisted by multipartite entanglement is exponentially more powerful than unrestricted quantum communication without preshared entanglement. Our result establishes a multipartite analogue of the communication separation previously established in the bipartite setting [40], thereby identifying multipartite entanglement as a resource for exponential communication savings.

Beyond communication complexity, our results have implications for bounded-storage cryptography with quantum side-information [41]. The multipartite communication protocol developed here naturally gives rise to a seeded randomness extractor involving multiple independent weak sources (i.e., non-uniform but with some guaranteed min-entropy). The communication lower bound of our multipartite task translates directly into a lower bound on the quantum side-information required to compromise the resulting extractor. In particular, our construction shows that preshared entanglement exponentially enhances the power of quantum side-information: compromising the extractor requires polynomial-size unentangled quantum memory, whereas exponentially smaller entangled quantum memory suffices. Consequently, our results establish an exponential separation between

* ananyaphys.c@gmail.com