


SciPost Physics Submission

Collimation of dense atomic beams by Swept Velocity Shelving

Francesca Famà [1,2,3⋆], Benedikt Heizenreder [2,3⋆], Ananya Sitaram [2,3], Camila Beli [2,3,4], Robert J.C. Spreeuw [2,3], Stefan A. Schäffer [2,3,4] and Florian Schreck [2,3†]

1 Istituto Nazionale di Ricerca Metrologica (INRiM), Turin, Italy
2 Van der Waals-Zeeman Institute, Institute of Physics, University of Amsterdam, Amsterdam, The Netherlands
3 QuSoft, Amsterdam, The Netherlands
4 NNF Quantum Computing Programme, Niels Bohr Institute, University of Copenhagen, Copenhagen, Denmark

† SVS@strontiumbec.com

⋆ *These authors contributed equally to this work.*

arXiv:2607.28873v1 [physics.atom-ph] 30 Jul 2026

Abstract

Engineering continuous, high-flux, and collimated atomic beams is a useful resource for metrology and material deposition. Developments in this area have been essential for the evolution of cold-atom based quantum experiments, yet the ubiquitous balanced-force methods such as transverse molasses cooling degrade at high atomic flux due to absorption-induced force imbalance. We introduce a collimation scheme that combines the use of a broadband transition for velocity shifting with a narrowband transition for velocity selection, enabling velocity-selective beam collimation without relying on balanced-power counter-propagating beams. Collimated atoms are shelved in a long-lived internal state, reducing the total light scattering and providing a state-heralded collimated beam. Simulations using strontium as a model system show a highly effective collimation process that does not suffer from absorption-induced force-imbalance and experimental results agree well with these predictions.

Contents

1 Introduction **2**

2 Theory and Simulation **3**
2.1 Optical Molasses 3
2.2 Swept velocity shelving 7
2.2.1 SVS operating principle 7
2.2.2 SVS numerical simulation 9

3 Experimental implementation **12**
3.1 Setup 12
3.2 Results 14
3.2.1 Characterization via normal-mode spectroscopy 14
3.2.2 Performance of the SVS scheme 15
3.2.3 Comparison with conventional molasses cooling 16

4 Conclusions and Outlook **17**