

Fast Quantum Algorithms for Learning Linear Threshold Functions

Aleksandrs Krivcenko* Tuyen Nguyen† Ronald de Wolf‡

arXiv:2609.40331v2 [quant-ph] 5 Oct 2026

Abstract

Linear threshold functions are $f_{w,\theta}(x) = \mathrm{sign}(\langle w, x\rangle - \theta)$, where the weight vector $w \in \mathbb{R}^n$ is a unit vector, $\theta \in \mathbb{R}$ is a threshold, and typically $x \in \mathbb{R}^n$ or $x \in \{-1,1\}^n$. When $\theta = 0$, the LTF is called homogeneous, and we write $f_w := f_{w,0}$. Such functions are among the most important objects in machine learning, since they serve to linearly discriminate positive and negative examples. We give three positive results about learning LTFs:

1. Suppose we can make real-domain queries, meaning we can compute $f_{w,\theta}(x)$ at any $x \in \mathbb{R}^n$ of our choice. We give a quantum algorithm that outputs a hypothesis with classification error at most ϵ under the standard Gaussian distribution, using $O(\log(n/\epsilon))$ membership queries and $\widetilde{O}(n)$ other gates. Then we have also learned $f_{w,\theta}$ up to error $O(\epsilon)$ when x is Gaussian. Classical algorithms need $\Omega(n\log(1/\epsilon))$ queries.
2. A homogeneous LTF f_w on domain $\{-1,1\}^n$ where w has only k positive nonzero entries of the same value, is the Majority function on the support of w. Belovs gave a bounded-error quantum algorithm that identifies the hidden support exactly (and hence learns f_w) using $O(k^{1/4})$ queries. We give an exponential improvement, using $O(\log k)$ queries.
3. Suppose we have a unitary U that can produce (discretized) *quantum examples* under Gaussian measure, corresponding to $\int_x \sqrt{\gamma_n(x)}|x\rangle|f_w(x)\rangle dx$. This is a weaker access model than membership queries. We give a quantum algorithm based on the efficient *Hermite transform* of Jain et al. to learn homogeneous LTFs f_w with error ϵ under the Gaussian distribution, using $O(n^{1/4}/\sqrt{\epsilon})$ applications of U and $U^\dagger$ and $\widetilde{O}\left(\frac{n^{5/4}}{\sqrt{\epsilon}} + \frac{n}{\epsilon^2}\right)$ other gates.

*QuSoft, CWI, the Netherlands, and Télécom Paris, Institut Polytechnique de Paris, France. Supported by the Unitary Foundation microgrant "Designing quantum query algorithms on a laptop", and the France Excellence Quantum Scholarship program awarded by IFNL. krivcenko@telecom-paris.fr and aleksandrs.krivcenko@gmail.com

†University of Technology Sydney, Ultimo, NSW, Australia. Work partially done while visiting QuSoft, CWI, the Netherlands. Supported by a scholarship from the Sydney Quantum Academy, PHDR06031. Tuyen.Q.Nguyen@student.uts.edu.au

‡QuSoft, CWI and University of Amsterdam, the Netherlands. Partially supported by the Dutch Research Council (NWO) through Gravitation-grant Quantum Software Consortium, 024.003.037. rdewolf@cwi.nl