




Perfect non-local quantum computation is impossible

Marten Folkertsma, Dmitry Grinko, Gina Muuss, and Florian Speelman

QuSoft, University of Amsterdam

30 September 2026

arXiv:2609.40228v1 [quant-ph] 30 Sep 2026

Abstract

Non-local quantum computation (NLQC) asks two parties to apply a joint operation to their quantum inputs using an entangled resource state and one round of simultaneous quantum communication. NLQC has applications across quantum information, including attacks on quantum position verification, communication complexity, and quantum gravity.

Every bipartite unitary has an approximate NLQC protocol with finite entanglement, and exact protocols are known for several structured families. However, it has remained open whether every fixed unitary admits an exact protocol with finite-dimensional resources. We show that, even for two qubits, Haar-almost every unitary does not admit such a protocol, even when the resource state and local operations are tailored to the target.

The proof first shows that smooth deformations of an exact protocol can only change its target by local unitaries. For a fixed architecture, semialgebraic geometry limits the exact protocols to finitely many connected families, so each architecture reaches only finitely many local-unitary orbits. Taking the union over all architectures, the exactly implementable unitaries form countably many local-unitary orbits. We also show that some natural targets do not admit a protocol: the controlled phase $\mathrm{diag}(1,1,1,e^{i\theta})$ has no exact protocol with finite-dimensional resources whenever $e^{i\theta}$ is transcendental, for instance for $\theta = 1$.

Our results also apply to localizable quantum measurements, whose outcome is obtained from local measurements on inputs and a shared entangled resource state without communication. A rank-one projective measurement in a Haar-random basis is almost surely not localizable with a finite-dimensional resource state and finitely many local outcomes.

1 Introduction

Suppose two parties, Alice and Bob, jointly want to perform a quantum operation on a bipartite quantum system, for instance a computation or a measurement whose outcome they both would like to learn. They could do this by bringing their systems together, or by using several rounds of communication, but what if they are only allowed an entangled resource state and *one round of simultaneous communication*?

This setting is called *non-local quantum computation* (NLQC), and a central question in this topic is: given a channel $\mathcal{N}_{AB}$, what are the resource requirements to implement this channel by an NLQC protocol? The obstacle here is specifically quantum: if the inputs were classical, the parties could simply send each other copies of their inputs, after which both could compute the target function; for quantum inputs, the no-cloning theorem rules this out.

Background and applications. Besides its foundational interest, NLQC has applications across quantum information. Protocols for NLQC give attacks on quantum position verification [KMS11, BCF+14], the resources needed for NLQC are connected to communication complexity [BFSS13, GMPY25] and information-theoretic cryptography [ABM+24, AKL+25],