

2020–
2022

Electronic Colloquium on Computational Complexity, Report No. 185 (2022)

ECCC

Randomized versus Deterministic Decision Tree Size

Arkadev Chattopadhyay* Yogesh Dahiya† Nikhil S. Mande‡
Jaikumar Radhakrishnan§ Swagato Sanyal¶

Abstract

A classic result of Nisan [SICOMP '91] states that the deterministic decision tree *depth* complexity of every total Boolean function is at most the cube of its randomized decision tree *depth* complexity. The question whether randomness helps in significantly reducing the *size* of decision trees appears not to have been addressed. We show that the logarithm of the deterministic decision tree size complexity of every total Boolean function on n input variables is at most the fourth power of the logarithm of its bounded-error randomized decision tree size complexity, ignoring a polylogarithmic factor in the input size. Our result has the following consequences:

- The deterministic AND-OR query complexity of a total Boolean function is at most the fourth power of its randomized AND-OR query complexity, ignoring a polylog n factor.
- The deterministic AND (OR) query complexity of a total Boolean function is at most the cube of its randomized AND (OR) query complexity, ignoring a polylog n factor. This answers a recent open question posed by Knop, Lovett, McGuire and Yuan [SIGACT News '21].
- The notion of *rank* of a Boolean function was defined in a classic work of Ehrenfeucht and Haussler [Information and Computation'89] in the context of learning theory, and is characterized by the logarithm of decision tree size up to a logarithmic factor in the input size. Our results confirm a recent conjecture (ignoring a polylog n factor) of Cornelissen, Mande and Patro [FSTTCS '22], that asserted the equivalence of randomized and deterministic analogs of rank, upto polynomial factors, for all total Boolean functions.
- Combined with the above-mentioned work of Ehrenfeucht and Haussler, our result implies that the class of functions computable by randomized decision trees of polynomial size, is PAC-learnable in quasi-polynomial time.

To obtain our main result on decision tree size, we introduce the notion of *block number* of a Boolean function, which can be thought of as a counting analog of *block sensitivity* of a Boolean function that played a central role in Nisan's result mentioned above.

*Tata Institute of Fundamental Research, Mumbai. Partially supported by the MATRICS grant MTR/2019/001633 of the Science & Engineering Research Board of the DST, India arkadev.c@tifr.res.in

†The Institute of Mathematical Sciences, Chennai yogeshdahiya@imsc.res.in

‡QuSoft and CWI, Amsterdam. Supported by the Dutch Research Council (NWO), as part of the Quantum Software Consortium programme (project number 024.003.037) nikhil.s.mande@gmail.com

§School of Technology and Computer Science, TIFR, Mumbai, and International Centre for Theoretical Sciences, TIFR, Bengaluru jaikumar@tifr.res.in

¶Indian Institute of Technology, Kharagpur. Supported by an ISIRD grant by SRIC, IIT Kharagpur swagato@cse.iitkgp.ac.in

ISSN 1433-8092