

Error correction with brickwork Clifford circuits

Twan Kroll[1] and Jonas Helsen[2]

[1] *Institute for Logic, Language and Computation, University of Amsterdam, Amsterdam, Netherlands*
[2] *Qusoft and Centrum Wiskunde & Informatica, Amsterdam, Netherlands*

(Dated: February 25, 2026)

We prove that random 1D Clifford brickwork circuits form (in expectation) good approximate quantum error correction codes in logarithmic depth. Our proof makes use of the statistical mechanics techniques for random circuits developed by Dalzell et al. [PRX Quantum 3, 010333], adapted extensively to our own purpose. We also consider exact error correction, where we give matching upper and lower bounds for the required depth in which random 1D Clifford brickwork circuits become error correcting.

arXiv:2602.20900v1 [quant-ph] 24 Feb 2026

I. INTRODUCTION

Quantum error correction is a key building block for large scale quantum computers. By encoding a number of logical qubits into a larger number of physical qubits, one obtains protection against the error seemingly inherent in the operation of physical qubits. Since Shor's development of the first error reducing quantum codes [26], a vast literature has been developed over the past three decades, constructing error correction codes with various beneficial properties such as low-weight checks, high encoding rate, high distance, and compatibility with spatial locality (with trade-offs existing between all these parameters).

In its exact form, QEC requires perfect recovery of an encoded state after suffering some unknown error and is characterized by the Knill-Laflamme conditions [16]. Relaxing the perfect recovery requirement by an approximate recovery criterion might be more suitable for practical purposes as codes that achieve approximate QEC can outperform exact error correcting codes in different ways [19]. In fact, limits on perfect recovery do not necessarily preclude approximate recovery guarantees [6]. A popular approximate QEC notion is to require high entanglement fidelity; for which the Knill-Laflamme conditions can be generalized [5] and is closely related to the average fidelity between the recovered state and logical state [9, 15, 18].

In analogy to the fruitful study of classical (linear) random codes, there has been substantial interest recently in *random* (stabilizer) quantum error correction codes. Already in 2013 Brown & Fawzi proved that Clifford circuits of depth $O(\log^3(n))$ in an all-to-all connected architecture form good (i.e. linear rate and distance) exact quantum error correction codes [4]. Such codes however are not geometrically restricted and far from LDPC. More recently Gullans et al. [10] provided numerical and analytical evidence that *geometrically local* random Clifford circuits are good approximate quantum error correction codes already at logarithmic depth. This work was very recently supplemented with an analytical proof [20] that a certain class of 1D geometrically local circuits, often called the superbrick architecture [25], are good approximate quantum error correction codes. The analysis of these superbrick circuits was inspired by the surprising finding in Schuster et al. [25], that such unitaries form so-called unitary k-designs (thus mimicking statistical aspects of fully random unitaries). However in the work of Liu et al. [20], the error correcting nature of the more natural architecture of brickwork random circuits (which is also the architecture discussed in Gullans et al., see Fig 2 for an illustration) was left open [24]. The main result of this work is to close this gap. To do this we lean on the statistical mechanics techniques developed in [7], which were also recently used to prove that these brickwork random circuits constitute state 2-designs [13]. Random circuits have a wide range of applications. These include randomized benchmarking [12, 14, 17], constructing unitary designs [3, 11, 25], quantum algorithms [2], and many-body and black-hole physics [1, 23, 27]. This work contributes to the broader endeavor of understanding random quantum circuits and their various applications.

II. RESULTS

Our main result is a proof that 1D brickwork Clifford circuits become approximate quantum error correction codes in depth $O(\log(n))$. Specifically we prove the following theorem for the ensemble $\chi_{\text{brick}}^{D(n)}$ of n-qubit random brickwork circuits of depth $D(n)$ consisting of 2-qubit Clifford gates.

